

Genie Compact
Fluorescent Lamps

*Ideal for wall sconces, table
lamps and floor lamps*

ENERGY SAVER



Energy saver genie pro-pack

Philips Genie Compact Fluorescent Lamps are the ideal energy saving light bulbs for wall sconces, table lamps and floor lamps.

Direct replacement for incandescent bulbs

- Compact size to fit in existing fixtures
- Economic energy saving alternative to a standard A19 incandescent
- Instant on

Long life

- Lasts 5 years*

* Based on an average daily usage of 3–4 hours per day, 7 days per week.

PHILIPS
sense and simplicity

Genie Compact Fluorescent Lamps

Ordering, Electrical and Technical Data

Product Number	Description	Volts	Nom. Watts	Approx. Incand. Equiv.	Base	Color Temp. (Kelvin)	CRI	Approx. Initial Lumens ¹	MOL (In.)	Diam. (In.)	Rated Avg. Life (Hrs.) ²	Min. Starting Temp.	Max. Ambient Temp.	
21053-4	Genie Pro-Pack 14W 6PK	120	14	60 A19	Med.	2700	82	800	5.11	1.7	8000	-22°F/-30°C	140°F/60°C	NEW!
21055-9	Genie Pro-Pack 18W 6PK	120	18	75 A19	Med.	2700	82	1100	5.25	1.9	8000	-22°F/-30°C	140°F/60°C	NEW!

Shipping Data

Product Number	SKU UPC (0-46677)	Outer Bar Code (5-00-46677)	Case Qty.	Case Weight (lbs.)	Case Cube (cu. ft.)	Pallet Qty.	SKUs Per Layer	Layers High	SKU Dimensions (W x D x H)(In.)	Case Dimensions (W x D x H)(In.)	Pallet Dimensions (W x D x H)(In.)
21053-4	21053-3	21053-8	4	8.42	0.390	320	64	5	3.9 x 5.9 x 5.5	8.5 x 12.4 x 6.4	37.9 x 45.7 x 32.0
21055-9	21055-7	21055-2	4	15.98	0.472	260	52	5	4.3 x 6.4 x 5.6	9.3 x 13.5 x 6.5	36.3 x 45.6 x 32.5

- 1) Approximate initial lumens. The lamp lumen output is based upon lamp performance after 100 hours of operating life under standard laboratory conditions.
 2) Average life under specified test conditions with lamps turned off and restarted no more frequently than once every 3 operating hours. Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Above specifications are subject to change without notice.

WARNINGS & CAUTIONS: Do not use with dimmers. Some electronic timer and photosensor switches contain dimming circuitry, so before using such a switch, check with its manufacturer to ensure compatibility with electronic CFL bulbs. Do not use with emergency exit fixtures or lights. Outdoor use requires a weather-protected fixture. Turn off power before changing bulb. This device complies with Part 18 of the FCC Rules.

Use in recessed cans or enclosed indoor fixtures could result in reduced lamp life.

Reliable operating temperature range -22F/-30C to 140F/60C.

Note: This product may cause interference with radios, televisions, telephones, or remote controls. If interference occurs, move this product away from device or plug into another outlet.

Bulb Type	Table/Floor Lamp	Outdoor Postlight	Wall Sconce	Surface Mount	Reading Lamp	Border Lights	Recessed Fixture	Open Hanging	Vanity Strip	Ceiling Fan
Decorative Twister	•		•		•			•		
Universal	•	•	•	•	•	•	•	•		
3-Way	•									
Reflector Flood							•	•		
Dimmable Reflector Flood							•	•		
Candle		•	•		•					•
Vanity & Decor Globe								•	•	•
Soft White Plus	•	•	•		•	•		•		•
Outdoor		•				•				
Bug-A-Way		•								
Circline	•									
Genie	•	•	•	•	•	•	•	•	•	•



© 2008 Philips Lighting Company. All rights reserved.
 Printed in USA 1/08
 P-5909
www.philips.com

Philips Lighting Company
 200 Franklin Square Drive
 P.O. Box 6800
 Somerset, NJ 08875-6800
 1-800-555-0050
 A Division of Philips Electronics North America Corporation



Philips Lighting
 281 Hillmount Road
 Markham, Ontario
 Canada L6C 2S3
 1-800-555-0050
 A Division of Philips Electronics Ltd.