

# Product data sheet

## Characteristics

# D325NT

Safety switch, general duty, fusible, 400A, 3 poles, 50 hp, 240 VAC, NEMA 1, fuse class T, neutral factory installed



### Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device Application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	400 A
Voltage Rating	240 V AC
Enclosure Rating NEMA	NEMA 1
Maximum Horse Power Rating	50 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 240.6

### Complementary

Short Circuit Current Rating	100 kA T
Fuse type	T
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + G)
Wire Size	AWG 1/0...600 kcmil aluminium/copper 2 x AWG 1/0...2 x 300 kcmil aluminium/copper
Tightening torque	340 Lbf.in (38.41 N.m) (AWG 1/0...750 kcmil) 340 lbf.in (38.41 N.m) (2 x AWG 1/0...2 x 300 kcmil)
Depth	8.88 in (225.55 mm)
Width	24.88 in (631.95 mm)
Height	45.12 in (1146.05 mm)
Net Weight	108.03 lb(US) (49 kg)

### Environment

Certifications	UL listed file E2875
----------------	----------------------

### Ordering and shipping details

Category	00059-MISC G/D SWITCHES
Discount Schedule	DE1A
GTIN	785901003649
Nbr. of units in pkg.	1
Package weight(Lbs)	111.00 lb(US) (50.349 kg)
Returnability	No
Country of origin	CA

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	45.12 in (114.6 cm)
Package 1 width	24.88 in (63.2 cm)
Package 1 Length	8.90 in (22.6 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------