

Rittal – The System.

Faster – better – everywhere.



SV 9342.200 Connection Adapters

State: 9/22/2025 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9342.200 - Connection Adapters

For busbar systems with 60 mm center-to-center distance.

Features

| | |
|---|---|
| Model No. | SV 9342.200 |
| Material | Cover: ABS Punched section: Polyamide Fire protection corresponding to UL 94-V0 |
| Color | RAL 7035 |
| Rated current max. | 63 A |
| Rated operating voltage | 690 V, 3~ |
| Electrical UL ratings (SCCR) | 65 kA - 600 V, fuse class J max. 60 A, JDDZ/7 65 kA - 480 V, manual motor controller max. 65 A, NLRV/7 |
| Cable outlet | Top |
| For bar systems with center-to-center spacing | 60 mm |
| Note | The technical data may vary for UL applications. UL approval only applies in conjunction with AC application The rated operating voltage for DC applications depends on the busbar arrangement in the busbar support 9340.050/9341.050/9342.050. |
| Number of poles | 3-pole |
| Dimensions | Width: 20 mm Height: 215 mm Width: 0.79 " Height: 8.46 " |
| Connection of round conductors, fine wire with wire end ferrule | 2.5 - 10 mm ² |
| Connection of round conductors, single-wire | 2.5 - 10 mm ² |

Features

| | |
|--|---|
| Connection of round conductors, multi-wire | 2.5 - 10 mm ² |
| Suitable for busbars | Height: 5, 10 mm Height: 0.2, 0.39 " |
| Packaging unit | 1 pc(s). |
| Net weight | 0.199 |
| Gross weight | 0.206 |
| Copper weight (kg per piece) | 0.019 |
| Customs tariff number | 85369010 |
| EAN | 4028177503595 |
| ETIM 9 | EC001531 |
| ECLASS 8.0 | 27370304 |

Approvals

| | |
|--------------|--|
| Approvals | ABS DNV-GL Lloyds Register of Shipping UL + C-UL (listed) |
| Explanations | Declaration of conformity Declaration of conformity UK |
