



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series high speed cylindrical fuse

FWC-6A10F

UPC:051712796415

Dimensions:

- **Height:** 10 MM
- **Length:** 38 MM
- **Width:** 10 MM

Weight:9 G

Warranties:

- Not Applicable

Specifications:

- **Type:** Fuse
- **Application:** DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
- **Voltage Rating:** 500 Vac/dc (35-800A only)
- **Voltage Rating Numeric:** 600 V
- **Amperage Rating:** 6A
- **Amperage Rating Numeric:** 6 A
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 700 Vdc
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 10 x 38 mm
- **Packaging Type:** Standard
- **Breaking Capacity:** 200 A
- **Clearing (I²T):** 30
- **Frequency Rating Maximum:** 62 HZ
- **Frequency Rating Minimum:** 45 HZ
- **Fuse Shape:** cylindrical
- **Fuse Indicator:** Non Indicating
- **Pre Arc (I²T):** 4
- **Release Characteristic:** Other
- **Utilization category:** aR (accompanied semiconductor protection)



- **Voltage Type:** AC/DC
- **Watt Losses:** 1.5
- **With Striker:** No

Supporting documents:

- [Product Catalog](#)
- [6AMP 600V AC FERRULE 10 X 38MM](#)

Certifications:

- UL Recognized
- CSA Certified

Product compliance:

- CE Marked