



SKU: IK-1/0N

UPC: 0783669021752

Features & Benefits:

Description:

Copper Split Bolt, Conductor Range for Equal Main & Tap 1/0-4 Sol, cULus

Specs

Dimensions

Height BX (IN)	2
Weight BX (LB)	1.77
Width BX (IN)	5.313
Wire Diameter Range Primary (IN)	0.204 - 0.375

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Poles	1
Number of Ports / Wireways	1

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range for Equal Run & Tap Str	1 Str - 3 Str
Conductor Range for Equal Run & Tap Sol	1 Sol - 4 Sol
Conductor Range for Minimum Tap with Maximum Run	14 Sol
Rebar Size(s) Main	NA

Material and Finish

Connector Finish	NA
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	NA
Wire Binding Hardware Material	NA

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
--	---



Wire Binding Screw Size	NA
Wire Binding Torque	385

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366902175

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Voltage

Voltage Rating	35 kV
----------------	-------