



SKU: SGB-250

UPC: 0783669960358

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 250-6, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Ports / Wireways	2
Wire Orientation	Parallel

Dimensions

Drive Size Main	3/16
Drive Type Main	Internal Hex
Height (IN)	1.703
Height BX (IN)	3.5
Length (IN)	1.81
Weight (LB)	0.233
Weight BX (LB)	11.65
Width (IN)	0.75
Width BX (IN)	5.875

Material and Finish

Clamping Hardware Finish	Nickel Strick, Zinc, Green Dye
Clamping Hardware Material	Stainless steel
Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Clamping Bolt Size	9/16-18
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	7/16

Wire Binding Torque

250 kcmil - 4 AWG = 150

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Dual Rated	Yes
NEMA Code	S-573-6
UPC Code	78366996035

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA