



**UPC Code :** 078477943557

**Country Of Origin :** Please Contact Customer Service.

**RoHS Compliant :** Yes

## IP710-D0Z

IllumaTech Slide Dimmer for LED 0-10V Power Supplies, 1200VA, 10A LED, 120/277 VAC

IllumaTech Slide Preset Electro-Mechanical 0-10V Slide Dimmer for use with LED or Fluorescent Ballasts and Power Supplies, suitable for use with Class 1 or Class 2 wiring, 1200VA @ 120VAC, 1500VA @ 277VAC, 10A LED/Electronic Ballast 120/277VAC, 60Hz, 50mAmps maximum sinking current, single pole or 3-way control when used with 3-way switch - White, Ivory & Light Almond

- INNOVATIVE – Designed for use with LED fixtures using 0-10V power supplies
- ADVANCED – No power pack required for switching
- EXCEPTIONAL – Superior quality and dimming performance
- FLEXIBLE – Can be used in a single-pole or 3-way installation (with a 3-way switch, sold separately)

### Technical Information

#### Product Features

**Action :** Standard ON/OFF

**Available Colors :** Ivory, White, Gray, Black, Brown, Light Almond, and Red

**Color :** White, Ivory, Light Almond

**Frequency :** 60Hz

**Load Rating :** 10A, 1200VA, 1500VA

**Load Type :** Electronic 0-10VDC Fluorescent and 0-10VDC LED Power Supply

**Ordering Notes :** White, Ivory, Light Almond Color Kits

**Preset :** Preset

**Protection :** Radio/TV Filter

**Standards and Certifications :** cCSAus

**Style Name :** Illumatech

**Switch Type :** Single-Pole & 3-Way

**Type :** Slide

**Voltage :** 120/277 VAC

**Wallplate :** Order Separately

**Warranty :** 5-Year Limited

### Features and Benefits

- Designed specifically for use with LED fixtures using 0-10V power supplies and Mark 7® 0-10V fluorescent ballasts
- Dual voltage 120V/277V; 50mAmps maximum sink current
- No power pack required for switching
- Provides single pole or 3-way lighting control when used with a 3-way switch
- Compatible with Decora Plus™ screwless and Decora standard designer wallplates (sold separately)
- Six product options in each box with three changeable faceplates and single pole or 3-way functionality when used with a 3-way switch
- Fluid slide movement allows fine adjustment of light level with minimal effort
- Captive wraparound slide bar remains securely attached

### Patents\*

N\_A

\*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

### SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc.**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):  
+1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-  
1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

Visit our Website at: [www.leviton.com](http://www.leviton.com)

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts/](http://www.leviton.com/international/contacts/)

