



HANGERMATE VERTICAL MOUNT SCREW FOR CONCRETE, 3/8" ROD, 5/16" SCREW, 2 1/4" SCREW

CATALOG NUMBER

HMZG730



FEATURES

End-drilled and tapped for attaching threaded components to concrete

Solid, one piece cold formed part; head cannot spin off or unscrew from body

Tapered threads allow for easy starting in pre-drilled hole

PRODUCT ATTRIBUTES

Material: Steel

Finish: Electrogalvanized

Rod Size: 3/8"

Screw Diameter: 5/16"

Screw Length: 2 1/4"

Drill Bit Diameter: 1/4"

Ultimate Static Load: 2,188 lb

ADDITIONAL PRODUCT DETAILS

Tested in 3650 psi concrete.

Appropriate safety factors should be applied for design purposes.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

nVent.com **CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER**

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.