



Ceramalux Non-ALTO

C100S54/M PH 12PK

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Warnings and Safety

- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General information	
Base	E26 [Single Contact Medium Screw]
Operating Position	Universal [Universal]
Main Application	General Lighting (G)
ANSI Code HID	S54
Footnotes HID 1	For use in fixtures which do not redirect a substantial portion of the energy toward the arc tube; otherwise very early failure is anticipated. (376)
Light technical	
Luminous Flux (Rated) (Min)	8400 lm
Luminous Flux (Rated) (Nom)	9200 lm
Lumen Maintenance 10000 h (Nom)	90 %
Design Mean Lumens	8550 lm
Chromaticity Coordinate X (Nom)	520
Chromaticity Coordinate Y (Nom)	420
Correlated Color Temperature (Nom)	2100 K
Luminous Efficacy (Rated) (Min)	84 lm/W
Luminous Efficacy (rated) (Nom)	92 lm/W

Color Rendering Index (Nom)	18
Operating and electrical	
Power (Rated) (Nom)	100.4 W
Lamp Current (Nom)	2.1 A
Ignition Supply Voltage (Max)	110 V
Re-Ignition Time (Min) (Max)	2 min
Ignition Time (Max)	5 s
Voltage (Max)	62 V
Voltage (Min)	45 V
Voltage (Nom)	55 V
Mechanical and housing	
Bulb Finish	Clear
Cap-Base Information	Brass [Brass Cap]
Bulb Material	Hard Glass
Bulb Shape	BD17 [BD17]

Ceramalux Non-ALTO

Approval and application

Mercury (Hg) Content (Max) 22 mg

Luminaire design requirements

Bulb Temperature (Max) 400 °C

Cap-Base Temperature (Max) 190 °C

Product data

Order product name C100S54/M PH 12PK

EAN/UPC - Product 046677467272


Order code 467274

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 12


Material Nr. (12NC) 928601143590

Net Weight (Piece) 73.000 g



Dimensional drawing

Product	D	C (max)
C100S54/M PH 12PK	55 mm	138 mm



C100S54/M PH 12PK

