



Main

Range of product	Multi 9
Product or Component Type	Connector
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 4

Complementary

Line Rated Current	63 A
[Ui] rated insulation voltage	1000 V
Connection pitch	0.71 in (18 mm)
Standards	UL 486E
Product certifications	CURus IEC
Color	White RAL 9001)
Connections - terminals	Screw terminal top connector 0.01...0.05 in ² (6...35 mm ²) rigid Screw terminal top connector 0.01...0.05 in ² (6...35 mm ²) flexible
Tightening torque	30.98 lbf.in (3.5 N.m)
Range compatibility	Multi 9 C60 C60BP comb busbar

Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192851
Nbr. of units in pkg.	1
Package weight(Lbs)	5.04 oz (143.0 g)
Returnability	Yes
Country of origin	DE

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.22 in (3.1 cm)
Package 1 width	3.58 in (9.1 cm)
Package 1 Length	4.41 in (11.2 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	25
Package 2 Weight	8.67 lb(US) (3.932 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.