



## Main

Range	Multi 9
Product or Component Type	Comb busbar
Accessory / separate part category	Connection accessory
Lines description	2L
Length in 18 mm modules	6

## Complementary

Number of ways	3 ways 2 L
Poles configuration for 1 way	1 x 2P
Connection pitch	0.71 in (18 mm)
Connector type	tooth
Distance between way	1.42 in (36 mm)
Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	115 A 104 °F (40 °C)
[Ue] rated operational voltage	480 V AC 50/60 Hz Ph/Ph 277 V AC 50/60 Hz Ph/N
[Ui] rated insulation voltage	1000 V AC 50/60 Hz UL 508
Mounting Mode	Horizontal
Mounting location	Top tunnel type terminals
9 mm pitches	12
Width	4.25 in (108 mm)
Color	Light gray RAL 7035)
Range compatibility	Multi 9 C60BP

## Environment

Standards	UL 508
Fire resistance	1760 °F (960 °C) 30 s ) IEC 60695-2-1
Pollution degree	3
IP degree of protection	IP20 with end-pieces and tooth covers

## Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192813
Nbr. of units in pkg.	1
Package weight(Lbs)	2.65 oz (75.0 g)
Returnability	Yes

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.79 in (2 cm)
Package 1 width	2.01 in (5.1 cm)
Package 1 Length	3.94 in (10 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Weight	17.80 lb(US) (8.075 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.