



### Main

Range of product	Multi 9
Product or Component Type	Connector
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 4

### Complementary

Line Rated Current	63 A
[Ui] rated insulation voltage	1000 V
Connection pitch	0.71 in (18 mm)
Standards	UL 486E
Product certifications	CURus IEC
Color	White RAL 9001)
Connections - terminals	Screw terminal top connector 0.01...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) rigid Screw terminal top connector 0.01...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) flexible
Tightening torque	30.98 lbf.in (3.5 N.m)
Range compatibility	Multi 9 C60 C60BP comb busbar

### Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192936
Nbr. of units in pkg.	1
Package weight(Lbs)	5.29 oz (150.0 g)
Returnability	Yes

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.10 in (2.8 cm)
Package 1 width	5.31 in (13.5 cm)
Package 1 Length	3.70 in (9.4 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	25
Package 2 Weight	8.99 lb(US) (4.076 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.