

# ATV930C22N4C

Variable speed drive, Altivar Process ATV900,  
ATV930, 220 kW, 400/480 V, w/o braking unit,  
IP00





## Main

|                                    |  |
|------------------------------------|--|
| Range of Product                   | Altivar Process ATV900   |
| Device application                 | Industrial Application   |
| Product or Component Type          | Variable speed drive   |
| Product destination                | Synchronous motors<br>Asynchronous motors  |
| Product specific application       | Process for industrial   |
| Variant                            | Standard version<br>Without braking chopper  |
| Phase                              | 3 phase  |
| Mounting Mode                      | Wall mount   |
| Communication Port Protocol        | Modbus serial<br>EtherNet/IP<br>Modbus TCP   |
| [Us] rated supply voltage          | 380...480 V - 15...10 %  |
| Motor power kW                     | 220.0 KW normal duty<br>160.0 kW heavy duty  |
| Maximum Horse Power Rating         | 350.0 Hp normal duty<br>250.0 hp heavy duty  |
| Continuous output current          | 302 A 2.5 kHz heavy duty<br>427 A 2.5 kHz normal duty  |
| EMC filter                         | Integrated<br>With EMC plate option  |
| IP degree of protection            | IP21   |
| Degree of protection               | UL type 1  |
| Option module                      | Slot A communication module Profibus DP V1<br>Slot A communication module PROFINET<br>Slot A communication module DeviceNet<br>Slot A communication module EtherCAT<br>Slot A communication module CANopen daisy chain RJ45<br>Slot A communication module CANopen SUB-D 9<br>Slot A communication module CANopen screw terminals<br>Slot A/slot B/slot C digital and analog I/O extension module<br>Slot A/slot B/slot C output relay extension module<br>Slot B 5/12 V digital encoder interface module<br>Slot B analog encoder interface module<br>Slot B resolver encoder interface module<br>Communication module Ethernet Powerlink |
| Discrete input logic               | 16 preset speeds   |
| Asynchronous motor control profile | Variable torque standard<br>Constant torque standard<br>Optimized torque mode  |
| Synchronous motor control profile  | Permanent magnet motor<br>Synchronous reluctance motor   |
| Maximum output frequency           | 599 Hz   |
| Switching frequency                | 1...8 kHz adjustable<br>2.5...8 kHz with derating factor   |
| Nominal switching frequency        | 2.5 kHz  |
| Line current                       | 397.0 A 380 V normal duty)<br>296.0 A 380 V heavy duty)<br>324.0 A 480 V normal duty)<br>246.0 A 480 V heavy duty)   |
| Apparent power                     | 247 KVA 480 V normal duty)<br>187 kVA 480 V heavy duty)  |
| Maximum transient current          | 453 A 60 s heavy duty)<br>512 A 60 s normal duty)  |

|                      |          |
|----------------------|----------|
| Network Frequency    | 50-60 Hz |
| Prospective line Isc | 50 kA    |

## Complementary

|  |  |
|--|--|
| Discrete input number                                | 10   |
| Discrete input type                                  | DI1...DI8 programmable, 24 V DC $\leq$ 30 V)3.5 kOhm<br>DI7, DI8 programmable as pulse input 0...30 kHz, 24 V DC $\leq$ 30 V)<br>STOA, STOB safe torque off, 24 V DC $\leq$ 30 V) $>$ 2.2 kOhm   |
| Discrete output number                               | 2  |
| Discrete output type                                 | Logic output DQ+ 0...1 kHz $\leq$ 30 V DC 100 mA<br>Programmable as pulse output DQ+ 0...30 kHz $\leq$ 30 V DC 20 mA<br>Logic output DQ- 0...1 kHz $\leq$ 30 V DC 100 mA   |
| Analogue input number                                | 3  |
| Analogue input type                                  | AI1, AI2, AI3 software-configurable voltage 0...10 V DC 30 kOhm 12 bits<br>AI1, AI2, AI3 software-configurable current 0...20 mA/4...20 mA 250 Ohm 12 bits   |
| Analogue output number                               | 2  |
| Analogue output type                                 | Software-configurable voltage AQ1, AQ2 0...10 V DC 470 Ohm 10 bits<br>Software-configurable current AQ1, AQ2 0...20 mA 500 Ohm 10 bits   |
| Relay output number                                  | 3  |
| Relay output type                                    | Configurable relay logic R1 fault relay NO/NC 100000 cycles<br>Configurable relay logic R2 sequence relay NO 1000000 cycles<br>Configurable relay logic R3 sequence relay NO 1000000 cycles  |
| Maximum switching current                            | Relay output R1 resistive, $\cos \phi = 1$ 3 A 250 V AC<br>Relay output R1 resistive, $\cos \phi = 1$ 3 A 30 V DC<br>Relay output R1 inductive, $\cos \phi = 0.4$ 7 ms 2 A 250 V AC<br>Relay output R1 inductive, $\cos \phi = 0.4$ 7 ms 2 A 30 V DC<br>Relay output R2, R3 resistive, $\cos \phi = 1$ 5 A 250 V AC<br>Relay output R2, R3 resistive, $\cos \phi = 1$ 5 A 30 V DC<br>Relay output R2, R3 inductive, $\cos \phi = 0.4$ 7 ms 2 A 250 V AC<br>Relay output R2, R3 inductive, $\cos \phi = 0.4$ 7 ms 2 A 30 V DC |
| Minimum switching current                            | Relay output R1, R2, R3 5 mA 24 V DC   |
| Physical interface                                   | Ethernet<br>2-wire RS 485  |
| Connector Type                                       | 2 RJ45<br>1 RJ45   |
| Method of access                                     | Slave Modbus TCP   |
| Transmission rate                                    | 10, 100 Mbits<br>4.8 kbps<br>9600 bit/s<br>19200 bit/s   |
| Transmission frame                                   | RTU  |
| Number of addresses                                  | 1...247  |
| Data format  | 8 bits, configurable odd, even or no parity  |
| Type of polarization                                 | No impedance   |
| 4 quadrant operation possible                        | False  |
| Acceleration and deceleration ramps                  | Linear adjustable separately from 0.01...9999 s  |
| Motor slip compensation                              | Not available in permanent magnet motor law<br>Can be suppressed<br>Adjustable<br>Automatic whatever the load  |
| Braking to standstill                                | By DC injection  |
| Brake chopper integrated                             | False  |
| Maximum Input Current per Phase                      | 397.0 A  |
| Maximum output voltage                               | 480.0 V  |
| Relative symmetric network frequency tolerance       | 5 %  |
| Base load current at high overload                   | 302.0 A  |
| Base load current at low overload                    | 427.0 A  |
| Power dissipation in W                               | Forced convection 5030 W 380 V 2.5 kHz<br>Natural convection 451 W 380 V 2.5 kHz   |
| With safety function Safely Limited Speed (SLS)      | True   |
| With safety function Safe brake management (SBC/SBT) | True   |
| With safety function Safe Operating Stop (SOS)       | False  |

|  |  |
|--|--|
| With safety function Safe Position (SP)            | False  |
| With safety function Safe programmable logic       | False  |
| With safety function Safe Speed Monitor (SSM)      | False  |
| With safety function Safe Stop 1 (SS1)             | True   |
| With sft fct Safe Stop 2 (SS2)                     | False  |
| With safety function Safe torque off (STO)         | True   |
| With safety function Safely Limited Position (SLP) | False  |
| With safety function Safe Direction (SDI)          | False  |
| Protection type                                    | Thermal protection motor<br>Safe torque off motor<br>Motor phase break motor<br>Thermal protection drive<br>Safe torque off drive<br>Overheating drive<br>Overcurrent between output phases and earth drive<br>Overload of output voltage drive<br>Short-circuit protection drive<br>Motor phase break drive<br>Overvoltages on the DC bus drive<br>Line supply overvoltage drive<br>Line supply undervoltage drive<br>Line supply phase loss drive<br>Overspeed drive<br>Break on the control circuit drive |
| Quantity per Set                                   | 1  |
| Width  | 17.32 in (440 mm)  |
| Height   | 47.05 in (1195 mm)   |
| Depth  | 14.96 in (380 mm)  |
| Net Weight   | 379.20 lb(US) (172 kg)   |
| Electrical connection                              | Control screw terminal 0.5...1.5 mm <sup>2</sup> AWG 20...AWG 16<br>Line side screw terminal 2 x 150 mm <sup>2</sup> 2 x 350 kcmil<br>Motor screw terminal 2 x 150 mm <sup>2</sup> 2 x 350 kcmil<br>DC bus screw terminal 2 x 150 mm <sup>2</sup> 2 x 350 kcmil  |
| Transmission Rate                                  | 10/100 Mbit/s Ethernet IP/Modbus TCP<br>4.8, 9.6, 19.2, 38.4 kbit/s Modbus serial  |
| Exchange mode                                      | Half duplex, full duplex, autonegotiation Ethernet IP/Modbus TCP   |
| Data format  | 8 bits, configurable odd, even or no parity Modbus serial  |
| Type of polarization                               | No impedance Modbus serial   |
| Number of addresses                                | 1...247 Modbus serial  |
| Supply   | External supply for digital inputs 24 V DC 19...30 V), <1.25 mA overload and short-circuit protection<br>Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection<br>Internal supply for digital inputs and STO 24 V DC 21...27 V), <200 mA overload and short-circuit protection  |
| Local signalling                                   | Local diagnostic 3 LED mono/dual colour)<br>Presence of voltage 1 LED red)<br>Embedded communication status 3 LED dual colour)<br>Communication module status 4 LED dual colour)   |
| Input compatibility                                | DI1...DI8 discrete input level 1 PLC EN/IEC 61131-2<br>DI7, DI8 pulse input level 1 PLC IEC 65A-68<br>STOA, STOB discrete input level 1 PLC EN/IEC 61131-2   |
| Discrete input logic                               | Positive logic (source) DI1...DI8), < 5 V, > 11 V<br>Negative logic (sink) DI1...DI8), > 16 V, < 10 V<br>Positive logic (source) DI7, DI8), < 0.6 V, > 2.5 V<br>Positive logic (source) STOA, STOB), < 5 V, > 11 V   |
| Sampling duration                                  | 2 Ms +/- 0.5 ms DI1...DI8) - discrete input<br>5 Ms +/- 1 ms DI7, DI8) - pulse input<br>1 Ms +/- 1 ms AI1, AI2, AI3) - analog input<br>5 ms +/- 1 ms AQ1, AQ2) - analog output   |
| Accuracy   | +/- 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input<br>+/- 1 % AQ1, AQ2 for a temperature variation 60 °C analog output   |
| Linearity error                                    | AI1, AI2, AI3 +/- 0.15 % of maximum value analog input<br>AQ1, AQ2 +/- 0.2 % analog output   |
| Refresh time                                       | Relay output R1, R2, R3)5 ms +/- 0.5 ms)   |
| Isolation  | Between power and control terminals  |

## Environment

|  |  |
|--|--|
| Operating altitude   | <= 3280.84 ft (1000 m) without derating<br>3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m  |
| Operating position   | Vertical +/- 10 degree   |
| Product certifications   | CSA<br>TÜV<br>UL   |
| Marking  | CE   |
| Standards  | UL 508C<br>EN/IEC 61800-3<br>EN/IEC 61800-5-1<br>IEC 61000-3-12<br>IEC 60721-3<br>IEC 61508<br>IEC 13849-1   |
| Maximum THDI   | <48 % full load IEC 61000-3-12   |
| Assembly style   | Enclosed   |
| Electromagnetic compatibility                                    | Electrostatic discharge immunity test level 3 IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3<br>Electrical fast transient/burst immunity test level 4 IEC 61000-4-4<br>1.2/50 µs - 8/20 µs surge immunity test level 3 IEC 61000-4-5<br>Conducted radio-frequency immunity test level 3 IEC 61000-4-6 |
| Environmental class (during operation)                           | Class 3C3 according to IEC 60721-3-3<br>Class 3S3 according to IEC 60721-3-3   |
| Maximum acceleration under shock impact (during operation)       | 150 m/s <sup>2</sup> at 11 ms  |
| Maximum acceleration under vibrational stress (during operation) | 10 m/s <sup>2</sup> at 13...200 Hz   |
| Maximum deflection under vibratory load (during operation)       | 1.5 mm at 2...13 Hz  |
| Permitted relative humidity (during operation)                   | Class 3K5 according to EN 60721-3  |
| Volume of cooling air  | 227192.03 Gal/hr(US) (860 m <sup>3</sup> /h)   |
| Overvoltage category   | III  |
| Regulation loop  | Adjustable PID regulator   |
| Insulation resistance  | > 1 MOhm 500 V DC for 1 minute to earth  |
| Noise level  | 73 dB 86/188/EEC   |
| Vibration resistance   | 1.5 mm peak to peak 2...13 Hz)IEC 60068-2-6<br>1 gn 13...200 Hz)IEC 60068-2-6  |
| Shock resistance   | 15 gn 11 ms IEC 60068-2-27   |
| Environmental characteristic                                     | Chemical pollution resistance class 3C2 EN/IEC 60721-3-3<br>Dust pollution resistance class 3S2 EN/IEC 60721-3-3   |
| Relative humidity  | 5...95 % without condensation IEC 60068-2-3  |
| Ambient air temperature for operation                            | 14...104 °F (-10...40 °C) without derating)<br>104...140 °F (40...60 °C) with derating factor)   |
| Noise level  | 73 dB  |
| Pollution degree   | 2  |
| Ambient air transport temperature                                | -13...158 °F (-25...70 °C)   |
| Ambient Air Temperature for Storage                              | -13...158 °F (-25...70 °C)   |

## Ordering and shipping details

|                       |                          |
|-----------------------|--------------------------|
| Category              | 22279-ATV950             |
| Discount Schedule     | CP4E                     |
| GTIN                  | 3606481154750            |
| Nbr. of units in pkg. | 1                        |
| Package weight(Lbs)   | 403.45 lb(US) (183.0 kg) |
| Returnability         | Yes                      |
| Country of origin     | CN                       |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Package 1 Height             | 25.59 in (65 cm)         |
| Package 1 width              | 22.83 in (58 cm)         |
| Package 1 Length             | 55.12 in (140 cm)        |
| Unit Type of Package 2       | PAL                      |
| Number of Units in Package 2 | 1                        |
| Package 2 Weight             | 403.45 lb(US) (183.0 kg) |
| Package 2 Height             | 25.59 in (65 cm)         |
| Package 2 width              | 22.83 in (58 cm)         |
| Package 2 Length             | 55.12 in (140 cm)        |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Upgradeability             | <a href="#">Upgraded Components Available</a>   |