

TPRPM009

Power interface module, TeSys island, 15A
AC-1, 9A AC-3, 4kW / 5hp



Main

Range of Product	TeSys
Product name	TeSys island
Device short name	TPRPM
Product or Component Type	Power module
Device presentation	Power module connected to an automation controller through a bus coupler Operational only when connected to a bus coupler
Function Available	Upstream voltage presence detection Electronic thermal overload protection Monitoring of currents Control of third party power devices when associated to TPRDG IO module
Product compatibility	TPRBC bus coupler TPRDG digital IO module TPRAN analog IO module
Poles description	3P
Motor power kW	2.2 KW 230 V AC 50 Hz 4 KW 380...415 V AC 50 Hz 4 KW 440 V AC 50 Hz 5.5 KW 500 V AC 50 Hz 5.5 kW 690 V AC 50 Hz
Motor power HP (UL / CSA)	0.33 Hp 120 V at AC 60 Hz for 1 phase 1 Hp 240 V at AC 60 Hz for 1 phase 2 Hp 208 V at AC 60 Hz for 3 phase 2 Hp 240 V at AC 60 Hz for 3 phase 5 Hp 480 V at AC 60 Hz for 3 phase 7.5 hp 600 V at AC 60 Hz for 3 phase
[Ue] rated operational voltage	<= 690 V AC 47...63 Hz
[Ie] rated operational current	9 A 122 °F (50 °C) <= 440 V AC-3 15 A 122 °F (50 °C) <= 440 V AC-1
[Ith] conventional free air thermal current	15 A 122 °F (50 °C)
[Ui] rated insulation voltage	690 V IEC 60947-4-1 600 V UL 60947-4-1 600 V CSA C22.2 No 60947-4-1
[Uimp] rated impulse withstand voltage	6 kV
Overvoltage category	III
Thermal protection adjustment range	0.18...9 A
Thermal overload class	Class 5...30
Reset	Remotely or automatically
[Uc] control circuit voltage	24 V DC supplied by the bus coupler
Current consumption	60 mA
Power dissipation in W	0.6 W at Ie

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Complementary

Protection type	Thermal overload protection Motor overheat Overcurrent Undercurrent Jam Long start Stall Rapid cycle lockout Phase loss Rapid restart lockout Phase reversal Phase unbalance Phase sequence Ground current
Monitoring type	Time device ON Number of faults Number of device power cycles Average current Iavg Average voltage Vavg Max current Imax Max voltage Vmax
Local signalling	For DS (device status) 1 LED (green/red) For LS (load status) 1 LED (green/red)
Standards	EN/IEC 60947-1 EN/IEC 60947-4-1 UL 60947-4-1 CSA C22.2 No 60947-4-1
Product certifications	CCC CSA EAC UL
Mounting mode	Horizontal and vertical 35 mm symmetrical DIN rail)
Connections - terminals	Screw-clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) AWG 16...AWG 12)rigid Screw-clamp terminals 2 0.00...0.01 in ² (1...4 mm ²) AWG 16...AWG 12)rigid Screw-clamp terminals 1 0.00...0.01 in ² (1.5...4 mm ²) AWG 16...AWG 12)flexible without cable end Screw-clamp terminals 2 0.00...0.01 in ² (1.5...4 mm ²) AWG 16...AWG 12)flexible without cable end Screw-clamp terminals 1 0.00...0.01 in ² (1...4 mm ²) AWG 16...AWG 12)flexible with cable end Screw-clamp terminals 2 0.00...0.00 in ² (1...2.5 mm ²) AWG 16...AWG 14)flexible with cable end
Tightening torque	15.05 Lbf.In (1.7 N.m) flat Ø 6 mm 15.05 lbf.in (1.7 N.m) Phillips No 2
Width	1.77 in (45 mm)
Height	4.76 in (121 mm)
Depth	4.53 in (115 mm)
Net Weight	0.56 lb(US) (0.255 kg)

Environment

Ambient air temperature for storage	-13...158 °F (-25...70 °C)
Ambient air temperature for operation	14...122 °F (-10...50 °C) without derating 122...140 °F (50...60 °C) with current derating
Relative Humidity	5...95 %
Operating altitude	0...6561.68 ft (0...2000 m) without derating
IP degree of protection	IP20
Pollution degree	2
Protective treatment	TC
Fire resistance	1760 °F (960 °C) UL 94 1562 °F (850 °C) IEC 60695-2-1 1202 °F (650 °C) IEC 60695-2-12
Shock resistance	15 gn 11 ms) IEC 60068-2-27

Vibration resistance	1.5 mm peak to peak 3...13 Hz) IEC 60068-2-6 1 gn 13...200 Hz) IEC 60068-2-6
Electromagnetic compatibility	Electrostatic discharge immunity test, level 3 8 kV air, 6 kV contact)EN/IEC 61000-4-2) Radiated RF field immunity test, level 3 10 V/m)EN/IEC 61000-4-3) Fast transient immunity test, level 4 4 kV)EN/IEC 61000-4-4) Surge immunity test, level 3 2 kV)EN/IEC 61000-4-5) Surge immunity test, level 4 4 kV)EN/IEC 61000-4-5) Conducted RF disturbance immunity test 20 V)EN/IEC 61000-4-6)

Ordering and shipping details

Category	22352-TESYS ISLAND LOAD CONTROLLERS
Discount Schedule	I12
GTIN	3606489832841
Nbr. of units in pkg.	1
Package weight(Lbs)	10.76 oz (305.0 g)
Returnability	No
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.97 in (5 cm)
Package 1 width	4.92 in (12.5 cm)
Package 1 Length	5.12 in (13 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	14
Package 2 Weight	10.11 lb(US) (4.584 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts product