



Main

Product or Component Type	Shunt trip
Circuit breaker type	M-frame R-Frame P-frame

Complementary

Rated voltage	380...480 V AC
Tightening torque	10.62 lbf.in (1.2 N.m) 0.00...0.00 in ² (0.82...2.5 mm ²) (AWG 18...AWG 14)

Environment

Product certifications	CSA
------------------------	-----

Ordering and shipping details

Category	01250-M,P,R FRAME ACCESSORIES ONLY
Discount Schedule	DE2
GTIN	785901306405
Package weight(Lbs)	8.00 oz (226.796 g)
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.