

Product data sheet

Characteristics

HOMT230240

Quad tandem circuit breaker, Homeline, 1 x 2 pole at 30A, 1 x 2 pole at 40A, 120/240VAC, 10kA AIR, plug in, UL



Main

Product	Miniature circuit-breaker
Range	Homeline
Current Rating	30 A 40 A
Certifications	UL Listed
Voltage Rating	120/240 V AC
Mounting Type	Plug-in
Number of Poles	2P
Short Circuit Current Rating	10 kA
Number of Spaces	2.0
Circuit Breaker Type	Quad tandem
Ratings	HACR rated
Electrical Connection	Box lugs
Wire Size	AWG 14...AWG 8 aluminium/copper)1 AWG 14...AWG 6 aluminium/copper)1

Complementary

Tightening torque	35.40...40.71 Lbf.In (4.0...4.6 N.m) 0.00...0.02 in ² (2.5...10 mm ²) (AWG 14...AWG 6) 35.40...40.71 lbf.in (4.0...4.6 N.m) 0.00...0.03 in ² (2.5...20 mm ²) (AWG 12...AWG 6)
Height	3.13 in (79.50 mm)
Width	1.97 in (50.04 mm)
Depth	3.29 in (83.57 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
---------------------------------------	----------------

Ordering and shipping details

Category	00046-HOM/T 15-30A 1P; 15-60A 2P
Discount Schedule	DE3D
GTIN	785901041009
Nbr. of units in pkg.	1
Package weight(Lbs)	16.00 oz (453.592 g)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	1.97 in (5 cm)
Package 1 Length	3.31 in (8.4 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration