

Product data sheet

Characteristics

EZML116125

Branch unit, EZ Meter-Pak, 125A, 6 sockets, 120/240 VAC, lever bypass, ringless, 800A Al busbar



Main

Product	Meter Center Branch Unit
Current Rating	125 A
Type	Meter-Pak
Bus Rating	800 A
Number of Jaws	5 with jaw release
Number of Meter Sockets	6
Bypass Type	Lever bypass
Socket Type	Ringless

Complementary

Busbar Material	Aluminium busbar
Short-circuit current	10 kA
Enclosure Rating	NEMA 3R
Maximum Voltage Rating	120/240 V AC
Mounting	Surface
Phase	1 phase in 1 phase out
Wire Configuration	3-wire
Height	75 in (1905.00 mm)
Width	15.38 in (390.65 mm)
Depth	8.95 in (227.33 mm)

Ordering and shipping details

Category	00020-EZ METER-PAK
Discount Schedule	DE4
GTIN	785901068167
Nbr. of units in pkg.	1
Package weight(Lbs)	180.78 lb(US) (82 kg)
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	8.94 in (227 mm)
Package 1 width	15.35 in (390 mm)
Package 1 Length	75.04 in (1906 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.