

DTU365DS

Safety switch, double throw, non fusible, 400A, 600 VAC, 250 VDC, 3 poles, 350 hp, NEMA 4, 4X, 5, 304 steel



Main

Product	Double Throw Safety Switch
Duty Rating	General duty
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Number of Poles	3
Current Rating	400 A
Voltage Rating	600 V AC 250 V DC
Enclosure Rating	NEMA 4/4X/5 stainless steel 304
Maximum Horse Power Rating	125 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 250 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 350 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC

Complementary

Short-circuit current	10 KA H or K 100 kA R, J or T
Fuse type	H or K R, J or T
Mounting Type	Surface
Wire Size	AWG 1/0...750 kcmil aluminium/copper
Tightening torque	550 Lbf.in (62.14 N.m) 0.08...0.47 in ² (53.49...304 mm ²) (AWG 1/0...750 kcmil) 62.14 lbf.in (7.02 N.m) 0.08...0.24 in ² (53.49...152 mm ²) (2 x AWG 1/0...2 x 300 kcmil)
Depth	7.25 in (184.15 mm)
Width	24 in (609.60 mm)
Height	54.50 in (1384.30 mm)
Net Weight	165.35 lb(US) (75 kg)

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	00134-DT SWITCH,NEMA12
Discount Schedule	DE1
GTIN	3606481716781
Nbr. of units in pkg.	1
Package weight(Lbs)	165.00 lb(US) (74.843 kg)
Returnability	No
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	54.49 in (138.4 cm)
Package 1 width	24.02 in (61 cm)
Package 1 Length	7.24 in (18.4 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile