



Main

Product	Surge protection device
---------	-------------------------

Complementary

Surge Current	200 A per phase
Voltage Rating	480 V delta AC
Number of Phases	3 phase
Wiring Configuration	3-wire (isolated ground)
MCOV	552 V
Rated Current	20 kA
Input voltage	1800 V L - G 2000 V N - G
Height	5.98 in (152 mm)
Width	5.98 in (152 mm)
Depth	3.98 in (101 mm)

Environment

Enclosure Rating	NEMA 4X
------------------	---------

Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	NULL
Nbr. of units in pkg.	1
Package weight(Lbs)	3.98 lb(US) (1.805 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.98 in (15.2 cm)
Package 1 width	5.98 in (15.2 cm)
Package 1 Length	3.98 in (10.1 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration