



Main

Range of Product	Square D
Product or Component Type	DOE 2016 energy efficient transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device application	Low voltage electrical distribution

Complementary

Box number	18M
Phase	3 phase
Rated operational power in VA	30 kVA
Network Frequency	60 Hz
Type of cooling	Natural convection
Primary voltage	480 V delta
Number of tap-offs	2 2.5 % FCAN 4 2.5 % FCBN
Primary operational current	180.42 A 416.36 A 150 kVA
Secondary voltage	208Y/120 V
Coil Material	Aluminium
Basic IMP level (BIL)	10 kV
Temperature Rise	150 °C 220 °C insulated
DOE Efficiency	98.29 % at 35 % load factor , 167 °F (75.0 °C)
Sound Level	6 DB NEMA ST-20 44 dB
%IZ	4.18 %
%IX	2.64 %
X/R Ratio	1.03
Inrush current	420 A
Let Through Current	1.99 kA
Transformer Losses	83 no load (core loss) 999 load loss (coil loss)
Transformer BTU/HR	378 16.6 % 496 25 % 1135 50 % 2201 75 % 3692 100 %
Height	28.31 in (719 mm)
Depth	24.69 in (627 mm)
Width	25.51 in (648 mm)
Net Weight	336.01 lb(US) (152.41 kg)
Mounting support	Floor Floor, with 7400FMB Ceiling, with 7400CMB18M19M20M Wall, with 7400WMB18M19M20M

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Degree of protection	UL type 2 UL type 3R, with 7400WS18M19M20M
Electrical connection	2 Hole Nema Pad secondary 0.44 in (11.1 mm) 4 Hole Nema Pad sec - XO 0.44 in (11.1 mm) 2 Hole Nema Pad primary 0.44 in (11.1 mm)
Number of mounting holes	0.51 in (13 mm)

Environment

Ambient Air Temperature for Operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	16259-3PH EXN/2016 K9 15-150KVA LVGP XFMR
Discount Schedule	PE2X
GTIN	785901413080
Nbr. of units in pkg.	1
Package weight(Lbs)	485.00 lb(US) (219.992 kg)
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	28.31 in (71.9 cm)
Package 1 width	25.51 in (64.8 cm)
Package 1 Length	24.69 in (62.7 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product