



# Compression Splice

By Burndy  
Catalog # YS39AM1

AL Splice, AL9CU, Internal Chamfer, Tin Plated, Prefilled PENETROX™ A13 oxide inhibitor, End Cap, UL/CSA, 90°C, Up to 35kV, Color Code, Die Index.



## Application

Wire Splice

## General

Color Code	Red
Connector Type	DUAL RATED
Die Index	936
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Long
Finish Type	Tin-Plated
Material	ALUMINUM
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYLINK
Temperature Rating	194
Trade Name	HYLINK™
Type	YS-A
UPC	781810766002
UPC 12 Digit	7818107660022

## Dimensions

Dimension - B Length fraction	2-5/8 in
Dimension - B Length inch	2.63 in
Dimension - L Length Overall mm	142 mm
Dimension - Length Overall inch	5.58 in
Dimension - Outside Diameter inch	1.60 in
Dimension - Strip Length inch Length	2-7/8 in 5.58 in
Outside Diameter	1.6 in

## Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

## Conductor Related

Conductor - AL Str Size	700 KCMIL- 750 KCMIL
Conductor - AL Str Size Range	700 kcmil-750 kcmil
Conductor - Copper Str Compact Size	700;750
Conductor - Copper Str Compact Size Range	700-750
Conductor - Copper Str Size	700 KCMIL; 750 KCMIL
Conductor - Copper Str Size Range	700 kcmil-750 kcmil
Conductor - Material	ALUMINUM / COPPER
Conductor Size	700 KCMIL-750 KCMIL
Conductor Type	CODE
Wire Size	700 KCMIL; 750 KCMIL

## Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

## Logistics

Carton Quantity	2
Minimum Pack Quantity	1

## Product Assets

- [3D Models - YS39AM1\\_MODEL-STEP](#)
- [3D Models - YS39AM1\\_MODEL-IGES](#)
- [3D Models - YS39AM1\\_MODEL-PDF](#)
- [Catalogs - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Sales Drawings - SD..073942-01](#)



A proud member of the Hubbell Family.

