



## Main

Product	Single Throw Safety Switch
Disconnect Type	Non-fusible disconnect
Number of Poles	3
Electrical Connection	Lugs
Duty Rating	Heavy duty

## Complementary

Line Rated Current	60 A
Factory Installed Neutral	None
Mounting Type	Surface
Voltage Rating	600 V AC/DC
Maximum Horse Power Rating	10 Hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 20 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 25 Hp 480 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 30 Hp 600 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 Hp 250 V at DC 30 hp 600 V at DC
Wire Size	AWG 14...AWG 3 copper or aluminium
Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in <sup>2</sup> (8.367 mm <sup>2</sup> ) (AWG 8) 40 Lbf.In (4.52 N.m) (AWG 8) 50 Lbf.In (5.65 N.m) 0.00...0.01 in <sup>2</sup> (2.06...5.261 mm <sup>2</sup> ) (AWG 14...AWG 10) 50 lbf.in (5.65 N.m) (AWG 14...AWG 10)
Height	16.5 in (419.10 mm)
Width	10.5 in (266.70 mm)
Depth	7 in (177.80 mm)

## Environment

Certifications	CSA
Enclosure Rating	NEMA 3R/12 galvanized steel

## Ordering and shipping details

Category	00153-C,CH&CHU CANADA SW NON-NEG
Discount Schedule	DE1
GTIN	785901994572
Nbr. of units in pkg.	1
Package weight(Lbs)	17.15 lb(US) (7.779 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.20 in (18.288 cm)
Package 1 width	10.60 in (26.924 cm)
Package 1 Length	19.90 in (50.546 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes