

CHU362AWKEI

Safety switch, heavy duty, non fusible, 60A,
600 VAC/VDC, 3 poles, 60 hp, NEMA 12,
interlock



Main

Range	Square D
Product	Single Throw Safety Switch
Current Rating	60 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	10 Hp 240 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 20 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 25 Hp 480 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 50 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 30 Hp 600 V at AC 50-60 Hz for 1 phase conforming to NEC 240.6 60 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 10 Hp 250 V at DC conforming to NEC 240.6 30 hp 600 V at DC
Disconnect Type	Non-fusible disconnect
Short Circuit Current Rating	10 kA
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Certifications	CSA
Voltage Rating	600 V AC/DC
Wire Configuration	4-wire
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper

Complementary

Tightening torque	50 Lbf.In (5.65 N.m) (AWG 3) 45 Lbf.In (5.08 N.m) (AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 50 lbf.in (5.65 N.m) 0.00...0.01 in ² (2.06...5.21 mm ²) (AWG 14...AWG 10)
Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Depth	7 in (177.80 mm)

Ordering and shipping details

Category	00113-H&HU SW,2&3P,N12,30-200A
Discount Schedule	DE1
GTIN	785901594567
Package weight(Lbs)	0.16 oz (4.536 g)
Returnability	No
Country of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes