


Product data sheet

Specifications



Extended rotary handle, ComPacT NSXm, red handle/yellow front, shaft length 200mm to 600mm, IP65

LV426934T

Product availability: Stock - Normally stocked in distribution facility

Main

Range compatibility	PowerPact PowerPact B ComPacT ComPacT NSXm
Product or Component Type	Rotary handle
Accessory / Separate Part Type	Control accessories
Handle colour	Red
Handle front plate colour	Yellow
Enclosure mounting style	Extended

Complementary

Rotary handle padlocking	Padlock in OFF position 1 to 3 padlocks
Product mounting position	Front
Locking options description	1 to 3 padlocks Ø 4 to Ø 8

Environment

IP Degree of Protection	IP65
-------------------------	------

Ordering and shipping details

Category	US10DE201136
Discount Schedule	0DE2
GTIN	3606481995247
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.54 in (9.000 cm)
Package 1 Width	3.54 in (9.000 cm)
Package 1 Length	17.91 in (45.500 cm)
Package 1 Weight	24.162 oz (685.000 g)
Unit Type of Package 2	S04
Number of Units in Package 2	12

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	15.75 in (40.000 cm)
Package 2 Length	23.62 in (60.000 cm)
Package 2 Weight	19.835 lb(US) (8.997 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) 6

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard Yes

Packaging without single use plastic No

[EU RoHS Directive](#) Pro-active compliance (Product out of EU RoHS legal scope)

SCIP Number Ab9dc4da-002c-433d-9974-4b46c472d129

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Halogen content performance Halogen free plastic parts product

Silicon free No

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back No

Offer Marketing Illustration

Product benefits / Features



Compact NSX Technical Benefits

- Come in one size and are optimized for small spaces.
- 3 or 4 pole versions
- Rated currents: 16 to 160 A
- Thermal-magnetic protections
- Breaking capacities under 240/415 V
16, 25, 36, 50, 70 kA
- Integrated earth leakage protection via MicroLogic Vigi (earth leakage circuit breaker - ELCB)
- EverLink™ connectors for bare cables

Offer Marketing Illustration

Product benefits / Features

CompacT NSXm Moulded Case Circuit Breaker



Efficiency

It features integrated earth leakage protection and standardized accessories – which means you save space, time, and effort.



Reliability

optimized in size and featuring innovations tailored to your needs. Roto-active™ breaking technology helps to increase operation lifespan.



Connectivity

Designed to connect to EcoStruxure Power, an IoT-connected architecture for improving every aspect of your power distribution system.



Offer Marketing Illustration

Product benefits / Features



Compact NSXm
Range Accessories

Wireless indication auxiliary

Long terminal shield

Standard auxiliary contact

Rotary handles

Inter-phase barrier

Toggle padlocking device

MN undervoltage release

Standard MX shunt release

The image displays a collection of accessories for the Compact NSXm circuit breaker range. At the top left, a green circular graphic contains a small image of the main circuit breaker. Below this, the title 'Compact NSXm Range Accessories' is presented in a large, bold font. The accessories are arranged in three rows. The first row includes a green wireless indication auxiliary, a long terminal shield, and a standard auxiliary contact. The second row features rotary handles and an inter-phase barrier. The third row contains a toggle padlocking device, an MN undervoltage release, and a standard MX shunt release. Each accessory is accompanied by a small image and a descriptive label.