



Overview

| | |
|-----------|------------------------------|
| Lead time | Usually Ships within 2 Weeks |
|-----------|------------------------------|

Main

| | |
|----------------------------|----------------|
| Rated power in W | 900 W |
| Rated power in VA | 1440 VA |
| Nb of power socket outlets | 8 NEMA 5-15R |
| Main Output Voltage | 120 V |
| Other Output Voltage | 110 V 125 V |
| Other Input Voltage | 110 V 125 V |
| Main Input Voltage | 120 V |
| Plug standard | NEMA 5-15P |
| Cable length | 6 ft (1.83 m) |
| Number of cables | 1 |

General

| | |
|-------------------------------------|--------------------------|
| Number of power module filled slots | 0 |
| Number of power module free slots | 0 |
| Product web sub-family | Cloud-enabled monitoring |
| Redundant | No |
| Provided equipment | USB cable |

Physical

| | |
|---------------------|------------------------|
| Mounting Location | Front |
| Mounting Mode | Not rack-mountable |
| Mounting preference | No preference |
| Depth | 17.28 in (43.9 cm) |
| Height | 8.62 in (21.9 cm) |
| Net weight | 44.31 lb(US) (20.1 kg) |
| Width | 6.73 in (17.1 cm) |
| Two post mountable | 0 |
| USB compatible | Yes |
| Color | Black |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Input

| | |
|-------------------------|-------------------------------------|
| Efficiency at full load | 85...136 V adjustable 93...130 V |
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |

Output

| | |
|----------------------------------|---------------------------------|
| Harmonic distortion | Less than 5% |
| Maximum configurable power in VA | 1440 VA |
| Max Configurable Power (Watts) | 900 W |
| Transfer Time | 6ms typical : 10ms maximum |
| Topology | Line Interactive |
| Waveform Type | Sine wave |
| Output Frequency (sync to mains) | 50/60 Hz +/- 3 Hz sync to mains |

Conformance

| | |
|-----------------------------|---|
| Product certifications | CULus ENERGY STAR V2.0 (USA) |
| Equipment protection policy | Lifetime : \$150000 |
| Standards | CSA C22.2 No. 107.1 FCC Part 15 class A ICES-003 UL 1778 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Acoustic level | 45 dBA |
| Heat dissipation | 225 Btu/h |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C) |
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |
| Relative Humidity | 0...95 % |
| Storage Relative Humidity | 0...95 % |

Batteries & Runtime

| | |
|------------------------------|-------------------|
| Battery type | Lead-Acid battery |
| Extendable Run Time | 0 |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Typical recharge time | 3 h |
| RBC Quantity | 1 |
| Battery life | 3...5 year(s) |
| Battery power in VAh | 288 VAh runtime |
| Battery Charge Power (Watts) | 96 W rated |

Communications & Management

| | |
|---------------|---|
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |
| Control panel | Multi-function LCD status and control console |
| Free slots | 0 |

Surge Protection and Filtering

| | |
|---------------------|---|
| Surge energy rating | 680 J |
| Filtering | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m |







Ordering and shipping details

| | |
|-----------------------|-----------------------------|
| Category | 11309 - APC RESALE PRODUCTS |
| GTIN | 00731304322764 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1 lb(US) (0.45 kg) |
| Returnability | No |

Packing Units

| | |
|------------------------------|------------------|
| Package 1 Height | 12.99 in (33 cm) |
| Package 1 width | 12.99 in (33 cm) |
| Package 1 Length | 23.23 in (59 cm) |
| Number of Units in Package 3 | 12 |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| Energy Star |  ENERGY STAR UPS V2.0 (USA) |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile |  End Of Life Information |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|