

# Product data sheet

## Characteristics

# GS2AH160

External rotary handle, TeSys GS, red handle, front mounting, 2 positions I-O, NEMA 3R, for GS 600-800A UL



### Main

|                           |                                |
|---------------------------|--------------------------------|
| Range of Product          | TeSys                          |
| Range                     | TeSys                          |
| Device short name         | GS2AH                          |
| Product or Component Type | Rotary handle                  |
| Range compatibility       | TeSys GS GS2S<br>TeSys GS GS2T |
| Type of operating handle  | External frontal               |
| Handle colour             | Red                            |
| Handle front plate colour | Yellow                         |

### Complementary

|                          |                       |
|--------------------------|-----------------------|
| Handle positions         | O-I                   |
| Rotary handle padlocking | With                  |
| Switch rated current     | 600 A<br>800 A        |
| Standards                | UL<br>CSA             |
| Net Weight               | 0.62 lb(US) (0.28 kg) |

### Environment

|                           |           |
|---------------------------|-----------|
| NEMA Degree of Protection | NEMA 4/4X |
|---------------------------|-----------|

### Ordering and shipping details

|                       |                              |
|-----------------------|------------------------------|
| Category              | 22640-IEC DISCONNECT-GS1,LK3 |
| Discount Schedule     | I11                          |
| GTIN                  | 3389119411905                |
| Nbr. of units in pkg. | 1                            |
| Package weight(Lbs)   | 9.88 oz (280.0 g)            |
| Returnability         | Yes                          |
| Country of origin     | FR                           |

### Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 2.76 in (7 cm)   |
| Package 1 width        | 3.54 in (9 cm)   |
| Package 1 Length       | 10.63 in (27 cm) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |                                                                                                                                                                                                                                |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                          |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                              |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                            |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>                                                                                                                                                                                  |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                            |
| Mercury free               | Yes                                                                                                                                                                                                                            |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                            |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                         |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                  |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                        |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|