

Project Name

Location

Prepared By



SATCO S29855

9W/LED/CFL/4CCT/BP/2P

Notes

(www) 09-14-2023 13:00:20

General

Status	Active
Watts	9W
Fluorescent Equivalent	18W/26W/32W
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	G24d (2-Pin)
ANSI Base	G24d
Finish	Frost
CCT (Kelvin)	2700K/3000K/3500K/4000K
Temperature	Warm to Cool White
CRI	80+
Lumens	1050L/1100L/1150L/1200L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	<20%
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	6.9
MOD	1.4
Housing Color	White
Weight (lb.)	0.22

Additional Information

Rated For Enclosed Fixture	Yes
Warranty	5-Years

Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp