



Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Analog output module
Analogue output type	0...20 mA or 4...20 mA +/- 10 V

Complementary

Analog/digital conversion	11 bits + sign 0...20 mA or 4...20 mA 11 bits +/- 10 V
Measurement resolution	0...20 mA or 4...20 mA +/- 10 V
Output load	<= 0.6 Ohm 0...20 mA or 4...20 mA >= 1 Ohm +/- 10 V
Protection type	Open-circuit 0...20 mA or 4...20 mA
Temperature drift	0.107 %/10 °C 0...20 mA or 4...20 mA 0.083 %/10 °C +/- 10 V
Current consumption	150 mA
Network type	1500 V AC

Ordering and shipping details

Category	22556 - TSX MICRO, PL7 MICRO & ACCESS
Discount Schedule	PC14
GTIN	00785901604525
Nbr. of units in pkg.	1
Package weight(Lbs)	2.21 lb(US) (1.00 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.17 in (5.5 cm)
Package 1 width	7.09 in (18 cm)
Package 1 Length	10.24 in (26 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	8
Package 2 Weight	11.22 lb(US) (5.088 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------

Wiring Diagram

