

Project Name

Location

Prepared By



# SATCO S29903

9T8/LED/24-850/BP 120-277V

## Notes

[www] 10-11-2021 02:00:31

### General

Status	Discontinued
Substitute	S39903
Watts	9W
Fluorescent Equivalent	17W
Volts	120V-277V
Ballast Type	Type B
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	24
Finish	Frost
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	82
Lumens	1150L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

### Electrical

Ballasting Requirements	Ballast Bypass
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

### Physical

MOL	24
MOD	1
Lens Finish	Frost
Weight (lb.)	0.24

### Additional Information

Additional Info	All glass tube
Tube Guard Use	Approved for use with tube guards
Installation Notes	Existing wiring to both sockets can remain in place. Will work on both shunted or non-shunted sockets.
Specification Note	Built-in shock resistant circuit - (not hot until both ends are installed)
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass

### Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLNVTKUDZ955
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes

Copyright 2020 Satco Products, Inc.  
All Rights Reserved

For More Information Visit:  
<http://www.satco.com/>

