



MASTERColor CDM-Rm Elite Mini

MASTERColor CDM-Rm Elite Mini 35W/930 GX10 MR16 25D

The Elite family is at the very top of the MasterColor CDM range, and gives a unique combination of unbeatable light quality and consistent performance over lifetime, while keeping running costs low. The MasterColor DCM Elite MR16 combines the familiar compact shape of MR16 halogen lamps with the performance of ceramic metal halide MasterColor Elite lamps. Suited for accent/decorative lighting, general lighting and downlighting in retail applications; or for outdoor landscaping and architectural effects.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General information	
Base	GX10 [GX10]
Operating Position	Universal [Universal]
Life to 5% Failures (Nom)	9000 h
Life To 10% Failures (Nom)	10000 h
Life to 20% Failures (Nom)	12000 h
Life to 50% Failures (Nom)	15000 h

ANSI Code HID	C130/O
Switching Cycle	1350X
Light technical	
Color Code	930 [CCT of 3000K]
Beam Angle (Nom)	25 °
Beam Angle Technical (Nom)	24 °

MASTERCOLOR CDM-Rm Elite Mini

Beam Angle Technical (Max)	29 °
Beam Angle Technical (Min)	19 °
Luminous Flux (Rated) (Min)	2180 lm
Luminous Flux (Rated) (Nom)	2340 lm
Luminous Intensity (Min)	5700 cd
Luminous Intensity (Nom)	7600 cd
Beam Description	-
Lumen Maintenance 12000 h (Nom)	85 %
Lumen Maintenance 2000 h (Nom)	95 %
Lumen Maintenance 4000 h (Nom)	93 %
Chromaticity Coordinate X (Nom)	0.439
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	60 lm/W
Color Rendering Index (Min)	88
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	80 %
Luminous Flux in 90° Cone (Rated)	2150 lm


Operating and electrical

Power (Rated) (Nom)	39.1 W
Re-Ignition Time (Min) (Max)	15 min
Warm Up Time to 60% Light (Nom)	120 s
Ignition Time (Max)	30 s
Voltage (Max)	95 V
Voltage (Min)	79 V
Voltage (Nom)	87 V

Controls and dimming

Dimmable	No
Run-Up Time 90% (Max)	3 min

Dimensional drawing



MASTERCOLOR CDM-Rm Elite Mini 35W/930 GX10 MR16 25D

Mechanical and housing

Bulb Shape	MR16 [2inch/50mm]
------------	--------------------

Approval and application

Mercury (Hg) Content (Nom)	4.7 mg
Energy Consumption kWh/1000 h	43 kWh

UV

Pet (Niosh) (Min)	8 h/500lx
Damage Factor D/fc (Max)	0.4

Luminaire design requirements


Reflector Neck Temperature (Max)	315 °C
----------------------------------	--------

Initial performance (IEC compliant)

Init. Color Rendering Index	90
-----------------------------	----

Product data


Order product name	MASTERCOLOR CDM-Rm Elite Mini 35W/930 GX10 MR16 25D
EAN/UPC - Product	046677418946
Order code	418947
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928194705315
Net Weight (Piece)	0.048 kg
ILCOS Code	MRS/UB-35/930-H-GX10-51/54.5/25





Product	D (max)	D	C (max)	C	C1 (max)	A (max)
MASTERCOLOR CDM-Rm Elite Mini 35W/930 GX10 MR16 25D	51 mm	50 mm	65.4 mm	62.75 mm	60.9 mm	59 mm

MASTERColor CDM-Rm Elite Mini


Photometric data




LDLD_CDM-Rm_35W_930_25D-Light distribution diagram



Lifetime



LDLE_CDM-Rm_35W_930-Life expectancy diagram



CDM-Rm 20W, 35W GX10 MR16

MASTERCOLOR CDM-Rm Elite Mini

