



CL501TN, Copper Lay-in Lug, Tin Plated

By Burndy
Catalog # [CL501TN](#)

Copper Lay-in Lug, 14-4 AWG, #10 Stud, Tin Plated.



Application

For Direct Burial Applications In Concrete Or Earth, For Fast Lay-In Of The Conductor Without The Need For Cutting Or Breaking, For Solar Panel Grounding

General

EU RoHS Indicator	Yes
Material	Copper
Material - Hardware	Stainless Steel
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	QIKLUG
Trade Name	QIKLUG
Type	Open-Faced
UPC	781810352342
UPC 12 Digit	7818103523422

Dimensions

Dimension - D inch	0.47 in
Dimension - Height inch	0.85 in
Dimension - Hole Size inch	0.22 in
Dimension - Hole Size mm	6 mm
Dimension - L Length Overall mm	29 mm
Dimension - Length Overall inch	1.13 in
Dimension - N inch	0.19 in
Dimension - Stud Size inch	17/64
Dimension - Thread Size	-
Dimension - Width inch	0.38 in
Dimension - Width mm	10 mm

Conductor Related

Conductor - Copper Solid Size	14 AWG;13 AWG;12 AWG;11 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Solid Size Range	14 AWG-4 AWG
Conductor - Copper Str Size	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - Copper Str Size Range	14 AWG - 4 AWG
Conductor Type	CU C Str-Size

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Listed Direct Burial	Y
Certification - UL Recognized	N
Certification - cULus	N
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Carton Quantity	700
Minimum Pack Quantity	100

Product Assets

[3D Models - CL501TN_MODEL-STEP](#)
[3D Models - CL501TN_MODEL-IGES](#)
[3D Models - CL501TN_MODEL-PDF](#)
[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - SC212515-01](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-CL501TN-SPEC-EN | REV 1/2024

