



Project:	Type:
Prepared By:	Date:

**Technical Specifications**

**Performance**

**Description:**  
Battery backup kit

**Compliance**

**UL Listed:**  
UL Listed

**UL 924:**  
Charge Time: 24 hours  
Emergency Run Time: 90 min

**California Energy Commission (CEC) Status:**  
CEC Title 20

**Construction**

**Finish:**  
Formulated for high durability and long-lasting color

**Electrical**

**Power Factor:**  
0.6@100Vac\_0.5@347Vac

**Emergency Wattage:**  
30W

**Input Voltage:**  
100-347VAC,50/60Hz

**Input Current:**  
0.15A max

**Input Power:**  
12W max

**Output Voltage:**  
120-200Vdc 250V MAX

**Battery Backup:**  
Rechargeable Lithium Ion

**Battery Recharge Time:**  
24 hours

**Ambient Temperature:**  
32°F to 122°F (0°C to 50°C)

**Battery Capacity:**  
14.8V/5200mAh

**Other**

**Compatible Products:**  
H17S, H17, H17XL

**5-Year Limited Warranty:**  
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

**Note:**

The EMHB is not compatible with all of the PIR40 Series, the MVS20 Series or the MVS50 Series.

Dimensions

