

Product data sheet

Characteristics

EZM1800CBU

Main unit, EZ Meter-Pak, 800A, 120/240VAC, 1 phase, 3 wire, 800A Al busbar, 65kA SCCR main breaker, under

Main

| | |
|---------------------------|--|
| Range of Product | EZ meter-pak |
| Product or Component Type | Meter center main unit |
| Main type | Main Circuit Breaker |
| Included Items | Closing plate Circuit-breaker2P 800 A 65 kA |

Complementary

| | |
|--------------------------------|--|
| Main rated current | 800 A |
| Bus rated current | 800 A |
| Material | Aluminium busbar |
| Enclosure Material | Steel |
| [Ue] rated operational voltage | 120/240 V AC |
| Device mounting | Surface |
| Number of Phases | 1 phase in 1 phase out |
| Service feed location | UG |
| Electrical connection | Lugs 1 AWG 6...300 kcmil aluminium/copper) ground Studs 2line Studs 2neutral |
| Wiring configuration | 3-wire |
| Height | 69.03 in (1753.36 mm) |
| Width | 20.46 in (519.68 mm) |
| Depth | 11.50 in (292.10 mm) |

Environment

| | |
|------------------------|-----------|
| Product Certifications | UL Listed |
| Enclosure Rating | NEMA 3R |

Ordering and shipping details

| | |
|-----------------------|----------------------------|
| Category | 00020-EZ METER-PAK |
| Discount Schedule | DE4 |
| GTIN | 785901304739 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 226.00 lb(US) (102.512 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 18.50 in (47 cm) |
| Package 1 width | 27.01 in (68.6 cm) |
| Package 1 Length | 72.09 in (183.1 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|