



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series fast-acting fuse

ABC-20-R

UPC:051712646222

Dimensions:

- **Height:** 1.25 IN
- **Length:** .25 IN
- **Width:** .25 IN

Weight:.008 LB

Notes:Ceramic body allows for higher amp/volt rating combinations.

Warranties: No Data

Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits
- **Voltage Rating:** 250 Vac, 125 Vdc, 32 Vac (self certified)
- **Amperage Rating:** 20A
- **Interrupt Rating:** 400 AIC at 250 Vac, 1 kAIC at 125 Vac, 10 kAIC at 125 Vdc
- **Connection:** Ferrule end X ferrule end
- **Material Type:** Ceramic tube, nickel-plated brass endcaps
- **Packaging Type:** Standard
- **Diameter:** .25 IN
- **Melting (L2T):** Typical pre-arc: 550.8
- **Resistance:** Typical DC cold: .00366 ohms
- **Voltage Drop:** Typical: .1 mV
- **Fuse Indicator:** Non Indicating
- **Response Time:** 4 hr minimum at 100%, 60 min maximum at 135%, 120 s maximum at 200%

Supporting documents:

- [BUSS SMALL DIMENSION FUSE](#)



Certifications: No Data

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.