



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series fast-acting fuse

ABC-30-R

UPC:051712542487

Dimensions:

- **Height:** 1.25 IN
- **Length:** .25 IN
- **Width:** .25 IN

Weight:.008 LB

Notes:Ceramic body allows for higher amp/volt rating combinations.

Warranties: No Data

Specifications:

- **Type:** Electronic
- **Application:** Electronic circuits
- **Voltage Rating:** 250 Vac, 125 Vdc, 32 Vac (self certified)
- **Amperage Rating:** 30A
- **Interrupt Rating:** 200 AIC at 250 Vac, 1000 AIC at 125 Vac, 400 AIC at 125 Vdc, 1 kAIC at 75 Vdc
- **Connection:** Ferrule end X ferrule end
- **Material Type:** Ceramic tube, nickel-plated brass endcaps
- **Packaging Type:** Standard
- **Diameter:** .25 IN
- **Melting (L2T):** Typical pre-arc: 1429
- **Resistance:** Typical DC cold: .002225 ohms
- **Voltage Drop:** Typical: .09 mV
- **Fuse Indicator:** Non Indicating
- **Response Time:** 4 hr minimum at 100%, 60 min maximum at 135%, 120 s maximum at 200%



Supporting documents:

- ROHS COMPLIANT

Certifications: No Data

Product compliance:

- RoHS Compliant
- CE Marked

© 2016 Eaton. All rights reserved.