



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Bussmann series time-delay fuse

**MDA-30-R**

**UPC:**051712542517

### Dimensions:

- **Height:** .25 IN
- **Length:** 1.25 IN
- **Width:** .25 IN

**Weight:**.006 LB

**Warranties:** No Data

### Specifications:

- **Type:** Electronic
- **Application:** Electronic Circuits
- **Voltage Rating:** 250 Vac, 125 Vdc
- **Amperage Rating:** 30A
- **Interrupt Rating:** 1.5 kAIC at 250 Vac, 10 kAIC at 125 Vac/dc
- **Connection:** Ferrule end X ferrule end
- **Material Type:** Ceramic tube, nickel-plated brass endcaps
- **Packaging Type:** Standard
- **Diameter:** .25 IN
- **Melting (L2T):** Typical: 1096.7
- **Resistance:** Typical DC cold: .002465 ohms
- **Voltage Drop:** Typical: .110 mV
- **Fuse Indicator:** Non Indicating
- **Response Time:** 60 min. maximum at 135%, 120 secs. maximum at 200%

### Supporting documents:

- [BUSS Small DIMENSION FUSE](#)

**Certifications:** No Data

### Product compliance:

- CE Marked



- RoHS Compliant

---

© 2016 Eaton. All rights reserved.