

Project Name

Location

Prepared By



SATCO S21404

PLT/16W/V/LED/830/4P/DR

Notes

[www] 10-11-2021 02:00:30

General

| | |
|------------------------|--------------------|
| Status | Active |
| Watts | 16W |
| Fluorescent Equivalent | 42W |
| Ballast Type | Type A |
| Shape | PL |
| Base | 4-Pin |
| ANSI Base | G24q |
| Finish | Frost |
| CCT (Kelvin) | 3000 |
| Temperature | Warm White |
| CRI | 82 |
| Lumens | 1750L |
| Beam Spread | 110 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Lamp Type | PL |
| Burning Position | Vertical Operation |
| Technology | LED |

Electrical

| | |
|-------------------------|---|
| Ballasting Requirements | Ballast required |
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to a maximum of +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 5.19 |
| MOD | 3.75 |
| Housing Color | White |
| Weight (lb.) | 0.35 |

Additional Information

| | |
|----------|--------------------------------|
| Warranty | 5 Year Limited - 10 hr per day |
|----------|--------------------------------|

Compliance

| | |
|-------------------|-----------------|
| Safety Listing | cULus |
| Location Rating | Damp |
| Energy Star | No |
| DLC Approved | Yes |
| DLC ID | PL4VNKVN27JE |
| California Status | Lawful for sale |
| RoHS Compliant | Yes |
| SDS Sheet | LED_Lamp |