



Main

| | |
|---------------------------|--------------------|
| Range | PratiKa |
| Product or Component Type | Interlocked socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 3P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| | |
|--------------------------------|---|
| Line Rated Current | 125 A |
| [Ue] rated operational voltage | 380...415 V |
| Network Frequency | 50/60 Hz |
| Protection Type | Residual current breaker with overcurrent protection (RCBO) |
| Plug, socket material | Housing self-extinguishing engineering polymer |
| Connections - Terminals | Captive screws |
| Cable cross section | 0.02...0.15 in ² (16...95 mm ²) |
| Cable entry | Cable gland |
| Thread type | Pg 42 |
| Net Weight | 24.47 lb(US) (11.1 kg) |
| Height | 27.95 in (710 mm) |
| Width | 10.63 in (270 mm) |
| Depth | 8.46 in (215 mm) |
| Color | Gray RAL 7035) |
| Voltage colour | Red |

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60309-2 EN 60309-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK08 EN 62262 |
| Fire resistance | 1760 °F (960 °C) IEC 60695-2-11 |
| Relative humidity | 50 % 104 °F (40 °C) 70 % 86 °F (30 °C) 90 % 68 °F (20 °C) |
| Ambient air temperature for operation | 95 °F (35 °C) 86400 s) |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |