



PL-C Cluster 4-Pin Base

PL-C 13W/841/4P/ALTO 10PK

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Warnings and Safety

- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: www.lamprecycle.org or 1-800-555-0050

Product data

General information	
Base	G24Q-1 [G24q-1]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %

Light technical	
Color Code	841 [CCT of 4100K]
Initial lumen (Nom)	925 lm
Luminous Flux (Rated) (Nom)	925 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4100 K

Luminous Efficacy (rated) (Nom)	69 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %

Operating and electrical	
Power (Rated) (Nom)	13.0 W
Lamp Current (Nom)	0.170 A

Temperature	
Design Temperature (Nom)	28 °C

PL-C Cluster 4-Pin Base

Controls and dimming

Dimmable Yes

Mechanical and housing

Cap-Base Information 4P

Approval and application


Mercury (Hg) Content (Nom) 1.4 mg

Energy Consumption kWh/1000 h 15 kWh


Product data

Order product name PL-C 13W/841/4P/ALTO 10PK

EAN/UPC - Product	046677240004
Order code	383281
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927907184030
Net Weight (Piece)	49.900 g
ILCOS Code	FSQ-13/40/1B-E-G24q=1




Dimensional drawing




PL-C 13W/841/4P/ALTO 10PK

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
PL-C 13W/841/4P/ALTO 10PK	27.1 mm	27.1 mm	97.5 mm	117.0 mm	131.9 mm

Photometric data





LDPB_PLC4P_840-Spectral power distribution B/W



LDPO_PLC4P_840-Spectral power distribution Colour


PL-C Cluster 4-Pin Base

Lifetime



LDLE_PLC4P_0001-Life expectancy diagram

LDLE_PLC4P_0002-Life expectancy diagram



LDLM_PLC4P_0001-Lumen maintenance diagram

