



**MILBANK**  
ENERGY AT WORK

## CP3B52119A22



|                               |                                                                                                    |
|-------------------------------|----------------------------------------------------------------------------------------------------|
| Catalog Number                | CP3B52119A22                                                                                       |
| Marketing Product Description | Ringless 200 Amperes 240 Volt 4 Terminal Main Circuit-breaker 24 Circuit Loadcenter 22k Mint Green |
| UPC                           | 784572319288                                                                                       |
| Length (IN)                   | 17                                                                                                 |
| Width (IN)                    | 16                                                                                                 |
| Height (IN)                   | 48                                                                                                 |
| Brand Name                    | Milbank                                                                                            |
| Type                          | Ringless Metered Commercial Pedestal                                                               |
| Application                   | Power Distribution                                                                                 |
| Standard                      | UL Listed;Type 3R                                                                                  |
| Voltage Rating                | 120/240 Volts Alternating Current                                                                  |
| Amperage Rating               | 100 Continuous Ampere                                                                              |
| Phase                         | 1 Phase                                                                                            |
| Frequency Rating              | 60 Hertz                                                                                           |
| Size                          | 17L x 16W x 48H                                                                                    |
| Number Of Cutouts             | 1                                                                                                  |
| Cutout Size                   | One 200 Ampere Main Breaker                                                                        |
| Cable Entry                   | Underground                                                                                        |
| Terminal                      | Single Mechanical                                                                                  |

|                           |                                              |
|---------------------------|----------------------------------------------|
| Insulation                | No Insulation                                |
| Mounting                  | Pad Mount                                    |
| Enclosure                 | G90 Galvanized Steel with Powder Coat Finish |
| Jaw Quantity              | 4 Terminal                                   |
| Bypass Type               | Lever Bypass                                 |
| Number of Meter Positions | 1 Position                                   |
| Equipment Ground          | Ground Bar                                   |
| Hub Opening               | No Hub Opening                               |
| Line Side Wire Range      | 6 AWG - 350 kcmil                            |
| Load Center               | 24 Circuit Load Center                       |
| Number Of Receptacles     | 0                                            |

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.