




**SKU:** ASN-2/0

**UPC:** 0783669184778

**Features & Benefits:**

**Description:** Surecrimp Aluminum Compression Sleeve, Conductor Size 2/0, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                         |             |
|-------------------------|-------------|
| Barrel Marking          | Hard        |
| Barrel Type             | Standard    |
| Connecting Angle        | 180°        |
| Connection              | Compression |
| Contains DE-OX®         | Yes         |
| Flared End              | No          |
| ILSCOs Die Index Number | 297         |
| Number of Conductors    | 1           |
| Sight Window            | No          |
| Slotted                 | No          |

### Dimensions

|                       |         |
|-----------------------|---------|
| Height (IN)           | 0.674   |
| Height BX (IN)        | 2.25    |
| Height (mm)           | 17.1196 |
| Inside Diameter (IN)  | 0.432   |
| Inside Diameter (mm)  | 10.9728 |
| Length (IN)           | 2.71    |
| Length (mm)           | 68.834  |
| Outside Diameter (IN) | 0.674   |
| Outside Diameter (mm) | 17.1196 |
| Weight (LB)           | 0.055   |
| Weight BX (LB)        | 0.6471  |
| Width (IN)            | 0.674   |
| Width BX (IN)         | 5       |
| Width (mm)            | 17.1196 |

### Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Stranded (Primary, run, main, line) | 2/0 Str         |
| Conductor Range CU Solid (Primary, run, main, line)    | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 2/0 Str         |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |
| Expanded Conductor Range                               | 2/0 Str - 1 Str |
| Flex Conductor Range                                   | NA              |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Copper   |
| Connector Finish   | Tin      |
| Material           | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated                  | Yes             |
| NEMA Code                   | S-588-1         |
| UPC Code                    | 78366918477     |

### Bolt and Screw Sizes

|                         |    |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|            |        |
|------------|--------|
| Color      | Silver |
| Color Code | Olive  |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|