



SKU: ASN-4/0

UPC: 0783669184792

Features & Benefits:

Description: Surecrimp Aluminum Compression Sleeve, Conductor Size 4/0, Tin Plated, UL, CSA

Specs

Dimensions

Height (IN)	0.854
Height BX (IN)	2.25
Height (mm)	21.6916
Inside Diameter (IN)	0.553
Inside Diameter (mm)	14.0462
Length (IN)	3.07
Length (mm)	77.978
Outside Diameter (IN)	0.854
Outside Diameter (mm)	21.6916
Weight (LB)	0.098
Weight BX (LB)	1.083
Width (IN)	0.854
Width BX (IN)	5
Width (mm)	21.6916

Additional Class Attributes

Barrel Marking	Hard
Barrel Type	Standard
Connection	Compression
Contains DE-OX®	Yes
Flared End	No
ILSCOs Die Index Number	467
Number of Conductors	1

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	4/0 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	4/0 Str - 1 Str
Flex Conductor Range	NA

Material and Finish

Conductor Material	Copper
Connector Finish	Tin

Material

Aluminum

Additional Technical Specifications

Conductor Type

Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366918479

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating

90°C

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating

35 kV