



|                |
|----------------|
| Catalog Number |
| Notes          |
| Type           |

Contractor Select™  
**FMLRL**

Low Profile Round  
 LED Flush Mount



With a low-profile, stay-white acrylic diffuser, the FMLRL LED flush mount provides general illumination for residential and light commercial applications such as kitchens, offices, utility work areas and stairways. The FMLRL is available in 11" and 14". Hidden cam-latches provide easy diffuser removal for installation and maintenance. Works with most standard incandescent dimmers.

**FEATURES:**

- Available in 2 color temperatures; 3000K and 4000K
- Dimmable to 10%
- Long life output eliminates routine maintenance



| Catalog Number    | UPC          | Description               | Replaces up to     | Lumens | Input Watts | CCT   | CRI | VOLTAGE | Pallet qty. |
|-------------------|--------------|---------------------------|--------------------|--------|-------------|-------|-----|---------|-------------|
| FMLRL 11 14840 M4 | 753573687405 | 11" Round LED Flush Mount | 75W Incandescent   | 1,100  | 16W         | 4000K | 80  | 120V    | 120         |
| FMLRL 14 20830 M4 | 820476883118 | 14" Round LED Flush Mount | 2-60W Incandescent | 1,600  | 24W         | 3000K | 80  | 120V    | 72          |
| FMLRL 14 20840 M4 | 753573687412 | 14" Round LED Flush Mount | 2-60W Incandescent | 1,600  | 24W         | 4000K | 80  | 120V    | 72          |

More configurations are available. Click here or visit [www.acuitybrands.com](http://www.acuitybrands.com) and search for LOW PROFILE ROUND LED

|   |                                    |
|---|------------------------------------|
| <b>Accessories:</b> Order as separate catalog number. |                                    |
| DFMLRL11  | 11" LED low profile round diffuser |
| DFMLRL14  | 14" LED low profile round diffuser |

**Compatible Dimmer Switches**

| Manufacturer | Part Number(s) |                |
|--------------|----------------|----------------|
| Leviton      | 6633P          | IPE04          |
|              | IPL06          | Trimatron 600W |
|              | 6674P          |                |
| Lutron       | DVELV 300P     | NTELV 300      |
|              | Skylark 300P   | NLV 300        |



## Specifications

---

### INTENDED USE:

Provides general illumination in commercial and residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more.

### CONSTRUCTION:

Features a white acrylic diffuser and is available in 11" and 14" sizes. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

### OPTICS:

11" Round units produce 1100 lumens and 14" Round units produce 1600 lumens, both at 50,000 hours life.

### ELECTRICAL:

Fixture operates at 120 volts, 60 Hz. 11" Standard input = 16 watts, 69 lumens per watt. 14" Standard input = 24 watts, 67 lumens per watt. Works with most standard incandescent dimmers (see list of approved dimmers).

### INSTALLATION:

All mounting hardware included.

### LISTINGS:

UL Certified to US and Canadian standards and listed suitable for damp locations. ENERGY STAR® certified.

### WARRANTY:

5-year limited warranty. Complete warranty terms located at:  
[www.acuitybrands.com/CustomerResources/Terms\\_and\\_conditions.aspx](http://www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx)

**Note:** Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

## Dimensions

---

### Round – FMRL 11

Height: 2-7/8 (7.3)

Width: 11 (27.9)

### Round – FMRL 14

Height: 3-1/8 (7.9)

Width: 13-11/16 (34.7)

All dimensions are inches (centimeters) unless otherwise indicated.