



**SKU:** ULT-3-Z

**UPC:** 0783669930740

**Features & Benefits:**

**Description:** Permagraund Copper Grounding C Crimp, Main Conductor Range 4-6 Sol, Tap Range 8 Str-8 Sol, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number	ND-BG

### Dimensions

Height (IN)	0.735
Height BX (IN)	2.25
Height (mm)	18.669
Length (IN)	0.47
Length (mm)	11.938
Weight (LB)	0.0353768071153485
Weight BX (LB)	3.89
Width (IN)	0.615
Width BX (IN)	5
Width (mm)	15.621

### Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 100
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366993074

### **Bolt and Screw Sizes**

Mounting Bolt/Stud Size	NA
-------------------------	----

### **Testing Standards**

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### **Environment and Temperature**

Temperature Rating	90°C
--------------------	------

### **Color**

Color	Copper
Color Code	NA

### **Conductor Ranges**

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol - 6 Sol
Conductor Range CU Solid (Secondary, tap, load)	8 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 6 Str
Conductor Range CU Stranded (Secondary, tap, load)	8 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

### **Voltage**

Voltage Rating	35 kV
----------------	-------