



## Switch Start Metal Halide Standard

Luminous Efficacy (Rated) (Min)	80 lm/W
Luminous Efficacy (rated) (Nom)	90 lm/W
Color Rendering Index (Nom)	57

### Operating and Electrical

Power (Rated) (Nom)	400 W
Lamp Current (Nom)	3.25 A
Ignition Supply Voltage (Min)	350 V
Re-Ignition Time (Min) (Max)	12 min
Ignition Time (Max)	120 s
Voltage (Max)	150 V
Voltage (Min)	120 V
Voltage (Nom)	135 V

### Mechanical and Housing

Bulb Finish	Clear
Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Bulb Shape	ED28 [ ED28]

### Approval and Application

Energy Saving Product	Not Applicable
Mercury (Hg) Content (Max)	52.0 mg


### Luminaire Design Requirements

Bulb Temperature (Max)	400 °C
Cap-Base Temperature (Max)	250 °C

### Product Data

Order product name	MH400/U/ED28 12PK
EAN/UPC - Product	046677426026
Order code	426023
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601151303
Net Weight (Piece)	0.001 kg

## Dimensional drawing



MH400/U/ED28 12PK

Product	D	C (max)
MH400/U/ED28 12PK	3.5 in	8.313 in

