



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series high speed cylindrical fuse

FWP-25A14F

UPC:051712795951

Dimensions:

- **Height:** 14 MM
- **Length:** 51 MM
- **Width:** 14 MM

Weight:21.2 G

Warranties:

- Not Applicable

Specifications:

- **Type:** Fuse
- **Application:** protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
- **Voltage Rating:** 700 Vac (IEC), 800 Vdc (UL), 690 Vac (IEC)
- **Voltage Rating Numeric:** 700 V
- **Amperage Rating:** 25A
- **Amperage Rating Numeric:** 25 A
- **Interrupt Rating:** 200 kAIC at 300 Vdc, 50 kAIC at 300 Vdc
- **Class:** Class aR
- **Color:** White
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 14 x 51 mm
- **Material Type:** Ceramic
- **Packaging Type:** Standard
- **Diameter:** 14 MM
- **Quantity:** 10
- **Used With:** Finger safe holders/blocks and striker
- **Breaking Capacity:** 200 A
- **Clearing (I₂T):** 320



- **Frequency Rating Maximum:** 62 HZ
- **Frequency Rating Minimum:** 45 HZ
- **Fuse Shape:** cylindrical
- **Fuse Indicator:** Non Indicating
- **Minimum Melting:** 46.5I2t (A2 Sec)
- **Pre Arc (I2T):** 49
- **Release Characteristic:** Other
- **Utilization category:** aR (accompanied semiconductor protection)
- **Voltage Type:** AC/DC
- **Watt Losses:** 7
- **With Striker:** No

Supporting documents:

- [Product Catalog](#)
- [25AMP 700V AC FERRULE 14.3 X 50.8MM](#)

Certifications:

- UL Recognized
- CSA Certified

Product compliance:

- CE Marked
- RoHS Compliant