


**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:

**SC956A4C0**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Sensing Window:  
 Far Limit:  
 Sensing Range: 120.0 mm to 2.0 m (4.7 in to 79.0 in)  
 Circuit Type:  
 Output Mode: Current  
 Volts Type: DC  
 Voltage Range: 15-24 VDC  
 Max Load: 10 - 500 ohm  
 Current Consumption: 80 mA  
 Sonic Frequency: 200 Hz  
 Temp Range: 0° to 50° C (32° to 122° F)  
 NEMA Type: 4X (indoor use only)  
 IP Rating: IP67  
 Standards: UL, CE Rohs

**Specification:**

Sensor Type: Ultrasonic Sensor  
 Description: Ultrasonic Sensor, Analog - Current (mA), 30 mm Barrel, 15-24 VDC  
 Body Style: Barrel  
 Diameter: mm  
 Housing Material:  
 Face Material: Silicone Rubber  
 Field Configurable: Yes, using AC441 Configurator and Superprox+ Software  
 Functionality: Configurable  
 Cable Size:  
 Connector Type: M12  
 Special Features: