

XCSM3702L5

Safety limit switch, Telemecanique Safety switches XCS, XCSM, metal, roller plunger, 2 NC + 1 NO, cable 5 m

Main

| | |
|-------------------------------|--|
| Range of Product | Telemecanique Safety switches XCS |
| Product or Component Type | Safety limit switch |
| Component name | XCSM |
| Design | Miniature |
| Material | Metal |
| Head type | Plunger head |
| Protection technology | Plastic protective cover, secured by 5-lobe socket head safety screw |
| Type of approach | Lateral approach |
| Type of operator | Roller plunger |
| Contacts type and composition | 1 NC + 1 NC + 1 NO |
| Contact operation | Slow-break, break before make |

Complementary

| | |
|--|--|
| Electrical Connection | Pre-cabled |
| Cable length | 16.4 ft (5 m) |
| Cable composition | 7 x 0.5 mm ² |
| Switch actuation | By 30° cam |
| Fixing Mode | By the body |
| Number of poles | 3 |
| Positive opening | With NC contact |
| Mechanical durability | 10000000 cycles |
| Minimum force for tripping | 7 N |
| Positive opening minimum force | 35 N |
| Minimum actuation speed | 6 m/min |
| Maximum actuation speed | 1.6 ft/s (0.5 m/s) |
| Contact code designation | B300, AC-15 (Ue = 240 V, Ie = 1.5 A)EN 60947-5-1 B300, AC-15 (Ue = 240 V, Ie = 1.5 A)EN/IEC 60947-5-1 appendix A R300, DC-13 (Ue = 250 V, Ie = 0.1 A)EN 60947-5-1 R300, DC-13 (Ue = 250 V, Ie = 0.1 A)EN/IEC 60947-5-1 appendix A |
| [Ui] rated insulation voltage | 300 VUL 508 400 V 3)IEC 60947-5-1 300 VCSA C22.2 No 14 |
| [Uimp] rated impulse withstand voltage | 4 KV IEC 60664 4 kV IEC 60947-1 |
| Maximum resistance across terminals | 25 MOhm IEC 60255-7 category 3 |
| Short-circuit protection | 6 A cartridge fuse gG (gl) |
| Repeat accuracy | 0.05 mm on the tripping points |
| Body Material | Zamak |
| Head material | Zamak |
| Depth | 0.6 in (16 mm) |
| Height | 2.8 in (70 mm) |
| Width | 1.2 in (30 mm) |
| Product Weight | 0.37 lb(US) (0.17 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|--|
| Standards | UL 508 EN/IEC 60204-1 EN 1088 EN/IEC 60947-5-1 CSA C22.2 No 14 |
| Product Certifications | CSA[RETURN]JUL |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach SIL 3 with the appropriate monitoring system and correctly wired IEC 61508 |
| Safety reliability data | B10d = 50000000 value given for a life time of 20 years limited by mechanical or contact wear |
| Protective treatment | TC |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 25 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 25 gn 18 ms IEC 60068-2-27 |
| Electrical shock protection class | Class I NF C 20-030 Class I EN/IEC 61140 |
| IP degree of protection | IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 IP68 conforming to IEC 60529 |
| IK degree of protection | IK06 conforming to EN 50102 |


Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US1000T22411 |
| Discount Schedule | 000T |
| GTIN | 3389110244199 |
| Returnability | Yes |
| Country of origin | ID |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.18 in (3 cm) |
| Package 1 Width | 8.66 in (22 cm) |
| Package 1 Length | 7.87 in (20 cm) |
| Package 1 Weight | 18.9 oz (537 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 20 |
| Package 2 Height | 11.81 in (30 cm) |
| Package 2 Width | 11.81 in (30 cm) |
| Package 2 Length | 15.75 in (40 cm) |
| Package 2 Weight | 25.452 lb(US) (11.545 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| Mercury free | Yes |
| RoHS exemption information |  Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|
