

# XMLK100P2D23

Electronic pressure sensors, Pressure sensors XM, sensor XMLK, 0...100 PSI, 1/4NPT, 4...20 mA, M12, set of 1

## Main

Range of Product	Telemecanique Pressure sensors XM
Product or Component Type	Electronic pressure sensors
Pressure sensor type	Pressure transmitter
Pressure sensor name	XMLK
Electrical circuit type	Control circuit
Pressure rating	100 psi (689.5 kPa)
Local display	Without
Controlled fluid	Air 32...176 °F (0...80 °C) Fresh water 32...176 °F (0...80 °C)
Fluid connection type	1/4" - 18 NPT (male)
Electrical connection	1 male connector M12 4 pins
[Us] rated supply voltage	24 V DC SELV 8...33 V
Current Consumption	< 20 mA
Type of output signal	Analogue
Analogue output function	4...20 mA, 2-wire
Quantity per Set	Set of 1
Type of Packing	Individual

## Complementary

Pressure setting range	0...100 psi (0.000000000...689.5 kPa)
Maximum permissible accidental pressure	200 psi (1379.0 kPa)
Destruction pressure	300 psi (2068.4 kPa)
Materials in contact with fluid	Stainless steel type AISI 303 Nitrile (NBR) Ceramic
Operating position	Any position
Protection Type	Reverse polarity Load short-circuit
Electromagnetic compatibility	Electrostatic discharge immunity test IEC 61000-4-2 8 kV air, 6 kV contact Susceptibility to electromagnetic fields IEC 61000-4-3 10 V/m 80...1000 MHz Electrical fast transient/burst immunity test IEC 61000-4-4 2 kV 1.2/50 µs shock waves immunity test IEC 61000-4-5 500 V 12 Ohm, 1 kV 42 Ohm Radiated RF fields IEC 61000-4-6 10 V 0.15...80 MHz Immunity to magnetic fields IEC 61000-4-8 30 A/m 50 Hz
[Uimp] rated impulse withstand voltage	0.5 kV
Response time on output	< 5 ms
Measurement accuracy	+/- 1 % of the measuring range
Resolution	0.1 % of the measuring range
Drift of the sensitivity	+/- 0.04 % of measuring range/°K
Drift of the zero point	+/- 0.03 % of measuring range/°K
Long term stability	+/- 1 % of the measuring range
Mechanical durability	10000000 cycles
Product Weight	0.24 lb(US) (0.11 kg)
Diameter	1.4 in (36 mm)
Length	2.6 in (65.5 mm)
Scale type	Fixed differential

## Environment

Standards	CE IEC 61326-2-3
Product Certifications	CSA C22.2 No 14[RETURN]RCM[RETURN]UL 508
Protective treatment	TC
Ambient Air Temperature for Operation	32...176 °F (0...80 °C)
Ambient Air Temperature for Storage	-13...176 °F (-25...80 °C)
Vibration resistance	20 gn 9...2000 Hz) IEC 60068-2-6
Shock resistance	25 gn 11 ms IEC 60068-2-27
IP degree of protection	IP65 conforming to IEC 60529
NEMA Degree of Protection	NEMA 4


## Ordering and shipping details

Category	US10DS221561
Discount Schedule	0DS2
GTIN	3389119048804
Returnability	Yes
Country of origin	CH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.57 in (4.000 cm)
Package 1 Width	3.23 in (8.200 cm)
Package 1 Length	6.38 in (16.200 cm)
Package 1 Weight	4.409 oz (125.000 g)
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Height	5.91 in (15 cm)
Package 2 Width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	6.989 lb(US) (3.170 kg)

## Offer Sustainability

SCIP Number	63bf6aac-e7ba-4853-b69a-9632a64b72b3
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes

## Contractual warranty

Warranty	18 months
----------	-----------