



Main

Range of product	Multi 9
Product or Component Type	OC contact
Device short name	OFS
Signal contacts composition	1 C/O
Line Rated Current	3 A 380...415 V AC - 50/60 Hz 6 A 220...240 V AC - 50/60 Hz 1 A 130 V DC 1.5 A 60 V DC 2 A 48 V DC 6 A 24 V DC
9 mm pitches	1

Complementary

Range compatibility	Multi 9 C60 C60BP Multi 9 C60 C60BPR Multi 9 C60 C60SP Multi 9 GFP GFP Multi 9 C60H-DC C60H-DC
Mounting Mode	Fixed
Mounting Support	DIN rail
Comb busbar and distribution block compatibility	Top YES
Height	3.31 in (84 mm)
Width	0.35 in (9 mm)
Depth	2.87 in (73 mm)
Connections - terminals	Clamp terminal 2 0.00 in ² (1.5 mm ²) - flexible Clamp terminal 2 0.00 in ² (1.5 mm ²) - rigid Clamp terminal 1 0.00...0.00 in ² (0.5...2.5 mm ²) - flexible Clamp terminal 1 0.00...0.00 in ² (0.5...2.5 mm ²) - rigid
Wire stripping length	0.35 in (9 mm)
Tightening torque	8.85 lbf.in (1 N.m)

Environment

Standards	EN/IEC 60947-5-1
Product Certifications	NEMKO DEMKO SEMKO CEBEC FIMKO
IP degree of protection	IP20 conforming to EN/IEC 60947-5-1
Pollution degree	3 EN/IEC 60947-5-1
Tropicalisation	2 EN/IEC 60947-5-1
Relative humidity	95 % 131 °F (55 °C)
Ambient Air Temperature for Operation	-13...122 °F (-25...50 °C)
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.




Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	3303430269236
Nbr. of units in pkg.	1
Package weight(Lbs)	1.52 oz (43.0 g)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	0.79 in (2 cm)
Package 1 Length	3.74 in (9.5 cm)
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Weight	12.55 lb(US) (5.694 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Unit Type of Package 3	BB1
Number of Units in Package 3	12
Package 3 Weight	20.60 oz (584.0 g)
Package 3 Height	3.54 in (9 cm)
Package 3 width	3.94 in (10 cm)
Package 3 Length	10.04 in (25.5 cm)

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------